

Applicable standard					
Rating	Operating Temperature range	-40 °C to +105°C (Note1)	Storage Temperature range	-10 °C to +60°C (Note2)	
	Operating Humidity range	20% to 80%	Storage Humidity range	40% to 70% (Note2)	
	Applicable connector	DF63W-*S-3.96C DF63WA-*S-3.96C	Voltage	AC/DC 630V	
	Applicable cable	AWG 16 to 18	Current	AWG 16 : 14A	
	Insulation diameter	φ 2.1 to φ 3.2mm		AWG 18 : 11A	
Specifications					
Item		Test method	Requirements	QT	AT
Construction					
General examination		Visually and by measuring instrument.	According to drawing.	X	X
Marking		Confirmed visually.		X	X
Electric characteristics					
Contact resistance		20mV MAX, 1mA (DC or 1000Hz).	10 mΩ MAX.	X	—
Mechanical characteristics					
Contact insertion and Extraction forces		T=1.14±0.002mm by steel gauge.	Insertion force 6.0N MAX Extraction force 0.3N MIN.	X	—
Mechanical operation		30 times insertion and extraction.	①Contact resistance: 20 mΩ MAX. ②No damage, crack or looseness of parts.	X	—
Vibration		Frequency 10 to 55 Hz, single amplitude 0.75 mm, at 10 cycles for 3 direction.	①No electrical discontinuity of 1 μs. ②No damage, crack or looseness of parts.	X	—
Shock		490 m/s ² duration of pulse 11 ms at 3 times each for 3 both axial directions.	①No electrical discontinuity of 1 μs. ②No damage, crack or looseness of parts.	X	—
Environmental characteristics					
Damp heat (Steady state)		Exposed at 40 ± 2°C , 90 to 95 %, 96 h. (After leaving the room temperature for 1-2h.)	①Contact resistance: 20 mΩ MAX. ②No damage, crack or looseness of parts.	X	—
Rapid change of temperature		Temperature -55°C→ +105°C Time 30min→ 30min Under 5 cycles. (The transferring time of the tank is 2-3 min) (After leaving the room temperature for 1-2h.)	①Contact resistance: 20 mΩ MAX. ②No damage, crack or looseness of parts.	X	—
<p>Note1: Include the temperature rising by current.</p> <p>Note2: Apply to the condition of long term storage for unused products before being processed of mounted on products. After before being processed or mounted on products, operating temperature and humidity range is applied for interim strage during transportation.</p>					
Count	Description of revisions		Designed	Checked	Date
0					
Remarks Unless otherwise specified, refer to IEC 60512.			Approved	HS. OKAWA	16. 07. 26
			Checked	TS. FUKUSHIMA	16. 07. 26
			Designed	YK. YAMAGUCHI	16. 07. 26
			Drawn	YK. YAMAGUCHI	16. 07. 26
Note QT:Qualification Test AT:Assurance Test X:Applicable Test			Drawing No.		ELC-359243-00-00
HS	Specification sheet		Part No.	DF63W-1618SC	
	HIROSE ELECTRIC CO., LTD.		Code No.	CL680-0601-8-00	△ 1/1