

Apr.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

1 2 3 4 5 6 7 8

A



B

C

D

E

F



- Notes.
1. 100 pcs. / pack
 2. Applicable cable dia : $\phi 1.7 \sim \phi 2.4$ mm
 3. The dimensions in parenthesis are reference dimensions.
 4. Always refer to the manuals below for operation of this product.
For cable assembly / ETAD-H0814

1	PBT	UL94V-0 (Black)	2	Silicone rubber	Green
NO.	MATERIAL	FINISH . REMARKS	NO.	MATERIAL	FINISH . REMARKS
UNITS mm		SCALE 2 : 1	COUNT 1	DESCRIPTION OF REVISIONS DIS-H-00000434	DESIGNED TO. HORII
HIROSE ELECTRIC CO., LTD.		APPROVED : HK. UMEHARA	15. 03. 10	DRAWING NO.	EDC-359259-00-00
		CHECKED : HK. UMEHARA	15. 03. 10	PART NO.	DF63WA-2S-3. 96C
		DESIGNED : TO. HORII	15. 03. 10	CODE NO.	CL680-0617-8-00
		DRAWN : TO. HORII	15. 03. 10		

FORM HC0011-5-7 1 2 3 4 5 6 7 8

A

B

C

D

E

F