

Applicable standard								
Rating	Operating temperature range	-55°C to + 85°C(Note 1)			Storage temperature range	-10°C to + 60°C(Note2)		
	Operating humidity range	20% to 80% (Note3)			Storage humidity range	40% to 70%(Note2)		
	Voltage	1000V AC/DC			Applicable Connector	DF22R -*S-7.92C(28) DF22#R-*S-7.92C		
	Current(*1)	Contact	2,3	4,5	Current(*2)	Contact	2,3	4,5
		AWG10	38A/pin	33A/pin		AWG10	25A/pin	22A/pin
		AWG12	32A/pin	26A/pin		AWG12	20A/pin	18A/pin
		AWG14	23A/pin	22A/pin		AWG14	18A/pin	15A/pin
		AWG16	21A/pin	19A/pin		AWG16	15A/pin	13A/pin
Rated voltage		Rated current			Overvoltage Category		IP-Protectio method	
UL	AC 600V	See above(*1) (At ambient temp.25°C)(Note 4)			—		—	
C-UL	AC 600V	See above(*2) (Temp. rise up 30°C MAX)			—		—	
TÜV	AC 600V	See above(*2)			II		IPOO	
Specifications								
Item		Test method			Requirements		QT	AT
Construction								
General examination		Visually and by measuring instrument.			According to drawing.		X	X
Marking		Confirmed visually.					X	X
Electric characteristics								
Contact resistance millivoltlevel method		20mV MAX, 1mA (DC OR 1000 Hz).			5 mΩ MAX.		X	—
Insulation resistance		1000V DC.			1000MΩ MIN.		X	—
Voltage proof		2500V AC for 1 min.			No flashover or breakdown.		X	—
Mechanical characteristics								
Mechanical operation		50times insertions and extractions.			1) Contact resistance: 10mΩ MAX. 2) No damage, crack or looseness of parts.		X	—
Vibration		Frequency 10 to 55 Hz, single amplitude 0.75 mm, at 2 h, for 3 directions.			1) No electrical discontinuity of 1μs. 2) No damage, crack or looseness of parts.		X	—
Shock		490 m/s ² duration of pulse 11 ms at 3 times for 3 directions.			1) No electrical discontinuity of 1μs. 2) No damage, crack or looseness of parts.		X	—
Environmental characteristics								
Rapid change of temperature		Temperature -55→ 5 to 35→+85→ 5 TO 35 °C Time 30→ 5 MAX → 30→ 5 MAX min Under 5 cycles.			1) Contact resistance: 10mΩ MAX. 2) Insulation resistance: 1000MΩ MIN. 3) No damage, crack or looseness of parts.		X	—
Damp heat (Steady state)		Exposed at 40 ± 2 °C, 90 to 95 %, 96 h.			1) Contact resistance: 10mΩ MAX. 2) Insulation resistance: 500MΩ MIN. 3) No damage, crack or looseness of parts.		X	—
Resistance to soldering heat		1) Solder bath method Solder temperature : 260°C for Immersion,duration : 10 sec . 2) Manual soldering Soldering iron temperature : 350°C Soldering time : 3 sec. No strength on contact.			No deformation of case of excessive looseness of the terminals.		X	—
Solderability		Soldered at solder temperature, 245°C for insertion duration, 5sec.			Solder shall cover a minimum of 95 % of the surface being immersed.		X	—
Remarks								
Note1: Including the temperature rising by current.								
Note2: No condensing.								
Note3: Apply to the condition of long term storage for unused products before mounted on PCB. After mounted on PCB, operation temperature and humidity range is applied for interim storage during transportation.								
Note4: Indicates the current that corresponds to the RTI value (temperature at which performance is halved) of the resin when the ambient temperature is 25°C.								
	Count	Description of revisions			Designed		Checked	Date
								
Unless otherwise specified , refer to IEC 60512.					Approved	HS. OKAWA	20200310	
					Checked	SZ. ONO	20200310	
					Designed	SN. MIWA	20200310	
					Drawn	DS. HIROWATARI	20200306	
Note QT:Qualification Test AT:Assurance Test X:Applicable Test					Drawing no.		ELC-306228-53-00	
	Specification sheet				Part no.	DF22R-*P-7. 92DS (53)		
	HIROSE ELECTRIC CO., LTD.				Code no.	CL010		
								1/1