



Mar.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.


HRS DRAWING FOR REFERENCE















NOTES 1 : LEAD CO-PLANARITY INCLUDE REINFORCED METAL FITTINGS SHALL BE 0.1mm MAX.
2 IF THE RESIST PROCESSING HAS NOT MADE, IT HAS POSSIBILITY THAT THE TERMINAL TOUCHES WITH ▨ AREA.
PLEASE BE NOTED THIS POINT.

MATED



MATED HIGHT (h) (mm)

HEADER NO. \ RECEPTACLE NO.	DF17#(3.0)-20DS-0.5V(57)	DF17#(4.0)-20DS-0.5V(57)
DF17(2.0)-20DP-0.5V(57)	5	6


NO.	MATERIAL	FINISH , REMARKS
8	POLYIMIDE	BROWN(HEAT-RESISTANCE TAPE)
7	PS	CLEAR (REINFORCEMENT COLLAR)
6	PS	BLACK (PLASTIC REEL)
5	POLYESTER	CLEAR (COVER TAPE)
4	PS	CLEAR (EMBOSSED CARRIER TAPE)
3	PHOSPHER BRONZE	TIN PLATED 1μm min UNDER PLATING : NICKEL 1μm min
2	POLYAMIDE (PA6T)	WHITE BEIGE , UL94V-0
1	PHOSPHER BRONZE	CONTACT AREA : GOLD PLATED 0.1μm min LEAD AREA : TIN PLATED 1μm min UNDER PLATING : NICKEL 1μm min

UNITS	SCALE		COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
mm	5 : 1	△0					

HIROSE ELECTRIC CO., LTD.


APPROVED	MO. ISHIDA	15.04.16	DRAWING NO. EDC-161716-58-58
CHECKED	TS. MIYAZAKI	15.04.16	PART NO. DF17(2.0)-20DP-0.5V(58)
DESIGNED	YN. SAKAMOTO	15.04.16	
DRAWN	YN. SAKAMOTO	15.04.16	CODE NO. CL683-0082-1-58 △0 1/2


Mar.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.




HRS DRAWING FOR REFERENCE

DIRECTION UNREELING





STYLE AND DIMENSION OF REEL (FREE)




DETAIL OF PART No. LABEL

SUPPLIER
QUANTITY
PART No.
CODE No.
DATE OF MANUFACTURED

生産月日	年　月　日
図番	CL683-0082-1-58
品名	DF17(2.0)-20DP-0.5V(58)
納入数量	1000Ko
納入者	ヒロセ電機(株)

D-D(FREE)



NOTES 3 : 1REEL : 1000 CONNECTORS.
4 : AT THE BEGINNING OF THE REEL , 30 COMPONENTS SHALL BE EMPTY.
AT THE END OF THE REEL, 20 COMPONENTS SHALL BE EMPTY.
5 : PEEL FORCE REFERS TO JIS C 0806(IEC60286-3).
6 ONE POCKET WIDTH IS BIGGER THAN OTHER IN CERTAIN DISTANCE.
7 AFTER PACKAGING, ROLL 2 METERS OF THE REINFORCEMENT COLLAR TO OUTER CIRCUMFERENCE OF TAPE AND REEL POCKET, AND TAPE DOWN AT THE END THE COLLAR.

DRAWING NO.	EDC-161716-58-58
PART NO.	DF17(2.0)-20DP-0.5V(58)
CODE NO.	CL683-0082-1-58

△0 2/2