



Mar.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.


















HRS DRAWING FOR REFERENCE

| CODE NO. | CONTACT | A | B | C | D | E | F | G | H | J |
|---|---|---|---|---|---|---|---|---|---|---|
| - | 20 | 10 | 6.7 | 5.6 | 4.5 | 9.8 | 8.2 | 7 | 10.4 | 7.6 |
| CL683-0257-3-57 | 26 | 11.5 | 8.2 | 7.1 | 6 | 11.3 | 9.7 | 8.5 | 11.9 | 9.1 |
| CL683-0272-7-57 | 30 | 12.5 | 9.2 | 8.1 | 7 | 12.3 | 10.7 | 9.5 | 12.9 | 10.1 |
| - | 40 | 15 | 11.7 | 10.6 | 9.5 | 14.8 | 13.2 | 12 | 15.4 | 12.6 |
| - | 50 | 17.5 | 14.2 | 13.1 | 12 | 17.3 | 15.7 | 14.5 | 17.9 | 15.1 |
| CL683-0365-6-57 | 60 | 20 | 16.7 | 15.6 | 14.5 | 19.8 | 18.2 | 17 | 20.4 | 17.6 |
| CL683-0397-2-57 | 70 | 22.5 | 19.2 | 18.1 | 17 | 22.3 | 20.7 | 19.5 | 22.9 | 20.1 |
| CL683-0373-4-57 | 80 | 25 | 21.7 | 20.6 | 19.5 | 24.8 | 23.2 | 22 | 25.4 | 22.6 |

NOTES 1 : LEAD CO-PLANARITY INCLUDE REINFORCED METAL FITTINGS SHALL BE 0.1mm MAX.
2 IF THE RESIST PROCESSING HAS NOT MADE, IT HAS POSSIBILITY THAT THE TERMINAL TOUCHES WITH ▨ AREA.
PLEASE BE NOTED THIS POINT.

| NO. | MATERIAL | FINISH , REMARKS |
|---|---|---|
| 7 | PS | CLEAR (REINFORCEMENT COLLAR) |
| 6 | PS | BLACK (PLASTIC REEL) |
| 5 | POLYESTER | CLEAR (COVER TAPE) |
| 4 | PS | CLEAR (EMBOSSED CARRIER TAPE) |
| 3 | PHOSPHER BRONZE | TIN PLATED 1μm min<br>UNDER PLATING : NICKEL 1μm min |
| 2 | POLYAMIDE (PA6T) | WHITE BEIGE , UL94V-0 |
| 1 | PHOSPHER BRONZE | CONTACT AREA : GOLD PLATED 0.1μm min<br>LEAD AREA : GOLD PLATED 0.02μm min<br>UNDER PLATING : NICKEL 1μm min |

| UNITS | SCALE | | COUNT | DESCRIPTION OF REVISIONS | DESIGNED | CHECKED | DATE |
|---|---|---|---|---|---|---|---|
| mm | 5 : 1 | 1 | 2 | DIS-H-007389 | NT. SEKI | YH. MICHIDA | 12.11.09 |


HIROSE ELECTRIC CO., LTD.


| | | |
|---|---|---|
| APPROVED | KH. IKEDA | 11.12.16 |
| CHECKED | TS. MIYAZAKI | 11.12.16 |
| DESIGNED | TR. YUNOKI | 11.12.16 |
| DRAWN | MS. SATO | 11.12.16 |

| | |
|---|---|
| DRAWING NO. | EDC3-162765-77 |
| PART NO. | DF17(1.0H)-*DP-0.5V(57) |
| CODE NO. | CL683- |


1 1/2

HIROSE ELECTRIC CO., LTD. All Rights Reserved.
Mar.1.2024 Copyright 2024 HIROSE
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.





STYLE AND DIMENSION OF REEL(FREE)






DETAIL OF PART NO. LABEL




| 生産月日 | 年　月　日 |
|---|---|
| 図　番 | CL683-****-*-57 |
| 品　名 | DF17(1.0H)-*DP-0.5V(57) |
| 納入数量 | 1000 Ko |
| 納入者 | ヒロセ電機（株） |

T-T(FREE)




DIRECTION OF REEL

| CODE NO. | CONTACT | L | M | N | P | Q |
|---|---|---|---|---|---|---|
| - | 20 | 24 | — | 11.5 | 10.3 | 25.5 |
| CL683-0257-3-57 | 26 | 24 | — | 11.5 | 11.8 | 25.5 |
| CL683-0272-7-57 | 30 | 24 | — | 11.5 | 12.8 | 25.5 |
| - | 40 | 24 | — | 11.5 | 15.3 | 25.5 |
| - | 50 | 32 | 28.4 | 14.2 | 17.8 | 33.5 |
| CL683-0365-6-57 | 60 | 32 | 28.4 | 14.2 | 20.3 | 33.5 |
| CL683-0397-2-57 | 70 | 44 | 40.4 | 20.2 | 22.8 | 45.5 |
| CL683-0373-4-57 | 80 | 44 | 40.4 | 20.2 | 25.3 | 45.5 |

NOTES 3 : 1REEL : 1000 CONNECTORS.
4 : AT THE BEGINNING OF THE REEL , 30 COMPONENTS SHALL BE EMPTY.
AT THE END OF THE REEL, 20 COMPONENTS SHALL BE EMPTY.
5 WHEN THE TAPE WIDTH IS 32mm or 44mm, SPROCKET HOLES SHALL BE SET ON BOTH SIDES OF REEL AS SHOWN ON THIS DRAWING.
△1 6 : PEEL FORCE REFERS TO JIS C 0806(IEC 60286-3).
7 ONE POCKET WIDTH IS BIGGER THAN OTHER IN CERTAIN DISTANCE.
8 AFTER PACKAGING, ROLL 2 METERS OF THE REINFORCEMENT COLLAR TO OUTER CIRCUMFERENCE OF TAPE AND REEL POCKET, AND TAPE DOWN AT THE END THE COLLAR.

HRS DRAWING FOR REFERENCE

| | | |
|---|---|---|
| HRS | DRAWING NO. | EDC3-162765-77 |
| | PART NO. | DF17(1.0H)-*DP-0.5V(57) |
| | CODE NO. | CL683- △1 2/2 |