Apr.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.



RECOMMENDED PATTERN



RECOMMENDED METAL MASK THICKNEES : 120μm
RECOMMENDED METAL MASK OPENING RATIO : 80% FOR LEAD PAD





A-A(20:1)



ENGAGEMENT FIGURE(20:1)



HRS DRAWING FOR REFERENCE

NOTE 1. ALL LEADS CO-PLANARITY SHALL BE 0.1 MAX.
2 ▨ IS NO PATTERN AREA OTHER THAN THE SAME CIRCUIT.
3 HRS MARK AND CAV NO. ARE LOCATED IN APPROXIMAL AREA.
4 GATE IS LOCATED IN APPROXIMAL AREA.
A PART OF THE WALL COULD BE NOTCHED FOR SETTING GATE.

部番	材質	処理，備考	部番	材質	処理，備考
2	COPPER ALLOY	CONTACT AREA:GOLD 0.05μm MIN	6	PS	CLEAR, REINFORCEMENT COLLAR
		SMT LEAD:GOLD 0.05μm MIN	5	PS	BLACK, PLASTIC REEL
		UNDERPLATING:NICKEL 1μm MIN	4	POLYESTER	CLEAR, COVER TAPE
1	LCP	BLACK, UL94V-0	3	PS	CLEAR, EMBOSSED CARRIER TAPE

UNITS	SCALE	△の数	訂正記事	設計	検図	年月日
mm	10 : 1	0				

HIROSE ELECTRIC CO., LTD.

承認	WR. FUKUCHI	18.03.05
検図	TS. MIYAZAKI	18.03.05
設計	SJ. WADA	18.03.05
製図	SN. NUMAZAKI	18.03.05

図番： EDC-319007-51-00
製品名： DF40HC(4.0)-40DS-0.4V(51)
製品コード： CL684-4111-6-51
0 1/2

Apr.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

EMBOSSED CARRIER TAPE(FREE)







DIRECTIONS OF UNREELING





7 TAPING

STYLE AND DIMENSION OF REEL(FREE)



8 DETAIL OF PART NO. LABEL

製造年月日	** ** **
製品コード	CL684-4111-6-51
製品名	DF40HC(4.0)-40DS-0.4V(51)
数量	2000
納入者	ヒロセ電機(株)

D-D (FREE)



NOTES
5. PER REEL 2000 CONNECTORS.
6. THE DIMENSIONS IN PARENTHESES ARE FOR REFERENCE.
7 REFER TO JIS C 0806(IEC 60286-3)(PACKING OF COMPONENTS FOR AUTOMATIC HANDLING)
8 DETAIL OF PART NO. LABEL IS WRITTEN IN JAPANESE.
PART NO. LABEL DESCRIBS THE FOLLOWING INFORMATION FROM TOP.
PRODUCTION DATE:
PRODUCT CODE: CL684-4111-6-51
PART NUMBER: DF40HC(4.0)-40DS-0.4V(51)
NUMBER OF PIECES: 2000 PIECES
SUPPLIER NAME: HIROSE ELECTRIC CO., LTD.
9 AFTER PACKAGING, ROLL 2 METERS OF THE REINFORCEMENT COLLAR TO OUTER CIRCUMFERENCE OF TAPE AND REEL POCKET, AND TAPE DOWN AT THE END THE COLLAR.

HRS DRAWING FOR REFERENCE

図番：	EDC-319007-51-00
製品名：	DF40HC(4.0)-40DS-0.4V(51)
製品コード	CL684-4111-6-51