



Mar.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.










HRS DRAWING FOR REFERENCE



NOTE
1. These are indicates the dimensions of after assembling
2. Ferrules are not included in this product. MU Ferrules are sold separately.
3. Apply adhesive to around the threads of R-shell-J(part No.1) before tighten Hood(part No.4).
4. Clamp ring has two holes for fixing hexagon socket screw.
   Tighten the screw at visible either hole with tightening torque 25N・cm. or either hole if both holes are visible.

NO.	MATERIAL	FINISH , REMARKS	NO.	MATERIAL	FINISH , REMARKS
6	STAINLESS STEEL	————			
5	PBT RESIN	COLOR:BLACK	11	SILICONE RUBBER	COLOR:BLACK
4	ALUMINUM ALLOY	ANODIC OXIDE COATING	10	ZINC ALLOY DIE CASTING	CHROME PLATING(COLOR:BLACK)
3	PIANO WIRE	ZINC PLATING * BAKING	9	PA RESIN	COLOR:WHITE
2	NITRILE BUTADIENE RUBBER	COLOR:BLACK	8	CHLOROPRENE RUBBER	COLOR:BLACK
1	ZINC ALLOY DIE CASTING	CHROME PLATING(COLOR:BLACK)	7	STAINLESS STEEL	————

UNITS	SCALE		COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
mm	2 : 1	△0					

HIROSE ELECTRIC CO., LTD.

APPROVED	MT. SHIBUTANI	18.02.02	DRAWING NO. EDC-177477-31-00
CHECKED	FS. YOSHIDA	18.02.02	PART NO. MF10B-WJ6.5CH01-0200(31)
DESIGNED	TY. SATO	18.02.02	
DRAWN	MK. INOUE	18.02.02	CODE NO. CL709-1035-5-31 △0 1/1