APPLICA	BLE STAN	DARD								
DATINO	OPERATING TEMPERATURE RANGE		-40°C TO +85°	С	STORAGE TEMPERATU		-25°C TO +70°C (AT	PACK	(ING)	
RATING	POWER		***		CHARACT IMPED					
			SPECI	IFICAT						
ITEM TEST METHOD REQUIREMENTS QT A										
CONSTR	RUCTION							I	I.	
GENERAL EXAMINATION		VISUALLY AND BY MEASURING INSTRUMENT.			۸۵۵۵	DDING TO		Х	Х	
MARKING		CONFIRMED VISUALLY.			ACCO	ACCORDING TO DRAWING.		X	X	
ENVIRONM	ENTAL CHARA	ACTERIST	rics					ı		
		PUT THE PRODUCT UNDER WATER FOR					CE.			
(MATING) 1		1 min. WITH AIR PRESSURE 4.9kPa.(IF			(67) NO AIR LLARAC		OL	X	-	
COUNT DESCRIPT		SCRIPTI	CRIPTION OF REVISIONS DE		ESIGNED		CHECKED	D/	ATE	
A 1	VI DE	DIS-K-00000296			S.YOSHIDA		YY.HIYAMA		16.06.02	
REMARK						APPROVE			06.03	
					CHECKED			10.06.03		
						DESIGNED	+		06.03	
						DRAWN	YH.MASUZAKI	_	06.03	
Note QT:Qualification Test AT:Assurance Test X:Applicable Test					DRAWING NO.		ELC4-176800-01			
ЖS	1	PECIFICATION SHEET			PART NO.		SW20-RC1(01)			
11/2	HIR	HIROSE ELECTRIC CO., LTD.			CODE NO. CL717-		17-5501-2-01	Λ	1/1	