May.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

ELV. RoHS COMPLIANT



HRS DRAWING FOR REFERENCE

△2 Packing specifications

1) How to connect carriers when reeling up
Max 6 joints per reel. Connect the carriers with interlayer paper.
At the begining of winding, fix the interlayer paper and carrier, and the reel core and paper with tape respectively.

2) Number of terminals
2500 terminals per reel.

3) Shortage
Max 20 missing terminal per reel.
Max 4 missing terminals per shortage. Min 6 terminals or more per carrier.

4) Reel dimensions & withdrawal direction



5) Storage state diagram



Storage state diagram

A-A



B-B

C-C



D-D



E-E



NO.	MATERIAL	FINISH . REMARKS	NO.	MATERIAL	FINISH . REMARKS
1	COPPER ALLOY	TIN PLATING	3	COPPER ALLOY	TIN PLATING
			2	PPS	BLACK

UNITS	SCALE		COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
mm	4 : 1	△2	1	DIS-T-00005803	NK. IKUTA	MO. OKADA	20200306

HIROSE ELECTRIC CO., LTD.

APPROVED	KI. HIROKAWA	20180324	DRAWING NO. EDC-373852-00-00
CHECKED	KI. HIROKAWA	20180324	PART NO. GT43-2428/1.6-2.9PCF
DESIGNED	NK. IKUTA	20180324	
DRAWN	DS. HIROWATARI	20180320	CODE NO. CL753-1004-0-00 △2 1/1