| APPLICA                                | BLE STANDA        | ARD  |                           |         |             |   |                   |            |              |
|--|-------------------|--|---------------------------|---------|-------------|---|-------------------|------------|--------------|
| OPERATING                              |                   |  | 40.00 TO 105.00           | (NOTE1) | STORAGE     |   | 40.0C TO 40       | F °C       |              |
| RATING                                 | TEMPERATURE RANGE |  |                           |         | TEMPERATU   | JRE RANGE   | -40 °C TO 105 °C  |            |              |
|  | VOLTAGE           |  | 250 V AC                  |         | CURRENT     |   | 1 A               |            |              |
|  |                   |  | SPECIFICATIONS            |         |             |   |                   |            |              |
| ľ                                      | TEM               |  | TEST METHOD               |         |             | REQUI   | REMENTS           | QT         | AT           |
| CONSTRU                                | JCTION            |  |                           |         |             |   |                   |            |              |
| GENERAL EXAMINATION                    |                   | VISUALLY AND BY MEASURING INSTRUMENT.                    |                           |         | ACCORDIN    | ACCORDING TO DRAWING.   |                   |            | ×            |
| MARKING                                |                   | CONFIRMED VISUALLY.                                      |                           |         |             |   |                   |            | ×            |
| ELECTRIC CHARACTE CONTACT RESISTANCE   |                   | <u> </u>   |                           |         | loo 0 144   | 30 m Ω MAX .  |                   |            | 1            |
| CONTACT RESISTANCE                     |                   | 1A DC.<br>20 mV AC MAX, 0.1 mA(DC OR 1000Hz)             |                           |         |             | 30 mΩ MAX.  |                   |            | _            |
| MILLIVOLT LEVEL METHOD                 |                   |  |                           |         | JOHN JE WIN |   |                   |            |              |
| INSULATION RESISTANCE                  |                   |  |                           |         | 1000 MΩ N   | 1000 MΩ MIN.  |                   |            | _            |
| VOLTAGE PROOF                          |                   | 650 V AC FOR 1 min.                                      |                           |         | NO FLASH    | NO FLASHOVER OR BREAKDOWN.  |                   |            | _            |
| MECHANICAL CHARAC                      |                   | <del>,</del>   |                           |         |             |   |                   | ×          | 1            |
| MECHANICAL OPERATION                   |                   | 30 TIMES INSERTIONS AND EXTRACTIONS.                     |                           |         | -           | <ul> <li>① CONTACT RESISTANCE: 60 m Ω MAX.</li> <li>② NO DAMAGE, CRACK AND LOOSENESS OF PARTS.</li> </ul> |                   |            | _            |
| VIBRATION                              |                   |  |                           |         |             | ① NO ELECTRICAL DISCONTINUITY OF 10 μs.   |                   |            | _            |
|  |                   | 1  |                           |         | -           | ② CONTACT RESISTANCE: 60 mΩ MAX. ③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS.                               |                   |            | _            |
| SHOCK                                  |                   | FREQUENCY 20 TO 50 Hz,<br>66.6 m/s <sup>2</sup> AT 1 h . |                           |         |             | ① NO ELECTRICAL DISCONTINUITY OF 10 μs.   |                   |            | -            |
|  |                   |  |                           |         | -           | 2 CONTACT RESISTANCE : $60 \text{ m}\Omega$ MAX .<br>3 NO DAMAGE, CRACK AND LOOSENESS OF PARTS.           |                   |            | -<br> -      |
| LOCK STRENGTH                          |                   | APPLYING A PULL FORCE THE MATING AXIALLY AT — N MAX.     |                           |         | _           | DURING APPLYING,MATING COMPLETELY.     AFTER APPLYING,NO DEFECT OF MATING PARTS.                          |                   |            | <br> -<br> - |
| ENVIRON                                | MENTAL CHA        |  |                           |         |             |   |                   |            | 1            |
| DAMP HEAT<br>(STEADY STATE)            |                   | EXPOSED AT 60 °C, 90 ~ 95 %, 96 h.                       |                           |         | ① CONTA     | CT RESISTAN   | CE : 60 m Ω MAX . | ×          | _            |
|  |                   |  |                           |         | -           | ② INSULATION RESISTANCE : 100 MΩ MIN.   |                   |            | -            |
| RAPID CHANGE OF<br>TEMPERATURE         |                   |  |                           |         |             | ③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS.<br>① CONTACT RESISTANCE: $60 \text{ m}\Omega$ MAX.             |                   |            | +-           |
|  |                   |  |                           |         | -           | ② INSULATION RESISTANCE: 100 MΩ MIN.  |                   |            | =            |
|  |                   | 11IVIL 30 / 3 / 30 / 3 IIIII                             |                           |         | ③ NO DAM    | (2) INSULATION RESISTANCE: 100 MΩ MIN. × (3) NO DAMAGE, CRACK AND LOOSENESS OF PARTS. ×                   |                   |            | -            |
| DRY HEAT                               |                   |  |                           |         | 1 2 NO DAN  | ① CONTACT RESISTANCE: 60 mΩ MAX.<br>② NO DAMAGE, CRACK AND LOOSENESS OF PARTS.                            |                   |            | _            |
| COLD                                   |                   | EXPOSED  | O AT -40°C, 120 h.        | ,       | A   ~       | ① CONTACT RESISTANCE: 60 mΩ MAX.<br>② NO DAMAGE, CRACK AND LOOSENESS OF PARTS.                            |                   |            | _            |
|  |                   |  |                           |         |             |   |                   |            |              |
| COUN                                   | T DE:             | SCRIPTION  | N OF REVISIONS            | Г       | ESIGNED     |   | CHECKED           | DA         | TE           |
| Z DEMARK                               |                   | DIS-T-00002745 TK. SH                                    |                           |         | SHISHIKURA  |   |                   |            | 2. 01        |
| REMARK (NOTE1) INCLUD                  | F THE TEMPERAT    | URE RISING   | ISING BY CURRENT.         |         |             | APPROVED  |                   | +          | 2. 19        |
| 1140200                                | L THE TENNI LIKAT | CILL MONVO   |                           |         |             | CHECKED   | KS. SATOH         | 07. 12. 19 |              |
|  |                   |  |                           |         |             | DESIGNED  |                   | _          | 2. 17        |
|  |                   |  |                           |         |             | DRAWN   | TY. IKEDA         | 07. 12. 17 |              |
| Note QT:Qualification Test AT:Assuranc |                   |  | ce Test X:Applicable Test |         |             | DRAWING NO. ELC-1668  |                   | 00-00      | )            |
| HS.                                    |                   |  | ATION SHEET               |         | PART NO.    |   |                   | <u> </u>   | 41.          |
| FORM HDOO                              |                   | JOE ELE  | ECTRIC CO., LTD.          | C       | ODE NO.     | CL75  | 8-0067-6-00       | <u>/1\</u> | 1/1          |