


Feb.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

ELV. RoHS COMPLIANT










MATED CONNECTORS

RECOMMENDED PANEL CUTOUT





RECOMMENDED PC BOARD PATTERN



RECOMMENDED REFLOW TEMPERATURE PROFILE

NOTE 1 A MUST BE TAKEN TO OBTAIN IMPEDANCE CHARACTERISTIC OF 50Ω.
2. THE RECOMMENDED REFLOW TEMPERATURE PROFILE IS AS FIGURE.
3. LEAD CO-PLANALITY INCLUDE REINFORCED FITTINGS SHALL BE 0.15mm MAX.

NO.	MATERIAL	FINISH , REMARKS	NO.	MATERIAL	FINISH , REMARKS
5	PPS	NATURAL			
4	PPS	NATURAL	9	PET	COVER TAPE
3	PHOSPHOR BRONZE	TIN PLATING	8	PS	EMBOSSED CARRIER TAPE
2	PHOSPHOR BRONZE	TIN PLATING	7	BRASS	TIN PLATING
1	PPS	BLACK	6	PHOSPHOR BRONZE	TIN PLATING

UNITS	SCALE		COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
mm	2 : 1	1	3	DIS-T-00006887	HK. WATANABE	MO. OKADA	20201022

HIROSE ELECTRIC CO., LTD.

APPROVED	KI. HIROKAWA	20200511
CHECKED	MO. OKADA	20200511
DESIGNED	HK. WATANABE	20200430
DRAWN	YK. MITSUISHI	20200309

DRAWING NO.	EDC-166246-55-00
PART NO.	GT16GD-1P-H(55)
CODE NO.	CL766-0044-5-55


1/2


FORM HC0011-5-7

HRS DRAWING FOR REFERENCE


Feb.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

DIRECTION OF UNREELING






HRS DRAWING FOR REFERENCE



NUMBER OF PRODUCTS : 200 PCS/REEL



DRAWING FOR PACKAGING

DRAWING NO.	EDC-166246-55-00
PART NO.	GT16GD-1P-H(55)
CODE NO.	CL766-0044-5-55

1 2/2