


Mar.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.


ELV. RoHS COMPLIANT







MATED CONNECTORS












RECOMMENDED PANEL CUTOUT





RECOMMENDED PC BOARD PATTERN

REFLOW TEMPERATURE PROFILE



NOTE 1. LEAD CO-PLANARITY SHALL BE 0.1mm MAX.
2. REFLOW TEMPERATURE PROFILE IS AS FIGURE.
3 MICROSTRIP LINE TO BE 50Ω FOR A DIMENSION.

NO.	MATERIAL	FINISH , REMARKS	NO.	MATERIAL	FINISH , REMARKS
2	COPPER ALLOY	TIN PLATING	4	COPPER ALLOY	TIN PLATING
1	COPPER ALLOY	TIN PLATING	3	PA	BLUE

UNITS	SCALE	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
mm	2 : 1	0				

HIROSE ELECTRIC CO., LTD.

APPROVED	KI. HIROKAWA	20200406	DRAWING NO. EDC-169969-55-00
CHECKED	MO. OKADA	20200406	PART NO. GT21T-1P-H(C)(55)
DESIGNED	HK. WATANABE	20200406	
DRAWN	YK. MITSUISHI	20200403	CODE NO. CL771-0067-6-55

0 1/2


FORM HC0011-5-7

HRS DRAWING FOR REFERENCE


Mar.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

ELV. RoHS COMPLIANT

PACKAGING SPECIFICATIONS (4:1)





HRS DRAWING FOR REFERENCE



A—A

REEL DIMENSIONS (FREE)





B—B

NOTE 4. 400 PIECES PER REEL.

HRS	DRAWING NO.	EDC-169969-55-00
	PART NO.	GT21T-1P-H(C)(55)
	CODE NO.	CL771-0067-6-55

0 2/2