




- Notes
- 1 The product is apply to the wire AWG#22 to 24(Wire jacket diameter:  $\phi 1.4$  to  $1.6$ )
  - 2 Per reel : 10,000 contacts.
  - 3  Surface plating : Tin plating  $1\mu\text{m}$  min.  
Under plating : Nickel plating  $1\mu\text{m}$  min.
  - 4 The assembly of this product applies to the manual ETAD-C0454-00.
  - 5  Bend the terminal and carrier up and down in the axial direction of the pilot hole to separate them.
  - 6  This product is coated with lubricant on the surface.  
Oil residues may be confirmed, but there is no problem with performance.  
In addition, if dust etc. adhere, remove it with an air blow or the like before using.

1	Copper alloy	3				
NO.	MATERIAL	FINISH . REMARKS		NO.	MATERIAL	FINISH . REMARKS
UNITS mm		SCALE 10 : 1	COUNT 	DESCRIPTION OF REVISIONS		DESIGNED SH. KOYAMA
			1	DIS-C-00009701		CHECKED EJ. KUNII
HIROSE ELECTRIC CO., LTD.		APPROVED : YH. YAMADA		DRAWING NO.		EDC-390467-00-00
		CHECKED : HN. TANAKA		PART NO.		BH12-P1-213
		DESIGNED : SH. KOYAMA		CODE NO.		CL0140-0017-0-00
		DRAWN : SH. KOYAMA				