



May.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

A
B
C
D
E
F




△ RECOMMENDED LAND PATTERN, METAL MASK DRAWING(5:1)
RECOMMENDED METAL MASK THICKNESS: t = 0.1




△數 COUNT	訂正事項 DISCRIPTION OF REVISIONS	擔當 B Y	檢圖 CHKD	年月日 DATE	△數 COUNT	訂正事項 DISCRIPTION OF REVISIONS	擔當 B Y	檢圖 CHKD	年月日 DATE
△ 2	RE-3-1760	KMJ	KHS	22.09.14	△				. . .
△ 1	RE-3-1863	KMJ	KHS	23.05.18	△				. . .
△				. . .	△				. . .

EMBOSSD TAPE DRAWING(4:1)



REEL DRAWING (SCALE FREE)





MATERIAL: PS(WHITE)

- NOTES:
- THE QUANTITY OF U.FL-R-SMT-K IS 10,000 CONNECTORS PER REEL.
 - LEAD CO-PLANARITY SHALL BE 0.1 MAX.
 - FOR THE POSSIBILITY OF BREAKAGE OR DEFORMATION DO NOT MATE THIS CONNECTOR WITH PARTNER, U.FL-LPK-*** BEFORE MOUNTING ON PC BOARD.
 - USE ALL PRODUCTS WITHIN 6 MONTHS AFTER THE DELIVERY.
STORE THEM IN MANUFACTURER'S PACKAGE OR TIGHTLY RE-CLOSED BOX WITH THE FOLLOWING CONDITIONS.
USE THIS PRODUCT WITHIN 6 MONTHS AFTER RECEIPT.
CHECK THE TERMINAL SODERABILITY BEFORE USE IF THE PRODUCT HAS BEEN STORED FOR MORE THAN 6 MONTHS.


TEPERATURE : -10°C TO +40°C
HUMIDITY : 15 TO 85% RH

5. ENBIRONMENTAL CONDITIONS
DO NOT USE THE PRODUCTS UNDER THE ENVIRONMENTAL CONDITION AS SHOWN BELOW DUE TO POSSIBLE DETERIORATION OF PRODUCTS.
SPECIAL GAS ATOMOSPHERE (HYDROGEN SULFIDE GAS, SULFUR SULFIDE GAS AND HYDROGEN CHLORIDE GAS)
PLACE ATTENTION REQUIRED: HEATING SYSTEM, AREA NEAR HOT SPRING, VOLCANIC MOUNTAIN AND ALIKE.
WATER SPLACHED AND CONDENSATION PLACES.
PLACE ATTENTION REQUIRED: HARSH TEMPERATURE CHANGE.


△3	LCP	UL 94V-0							
1	PHOSPHOR BRONZE	GOLD PLATING	△2	BRASS	GOLD PLATING				
NO.	MATERIAL	FINISH . MARKS	NO.	MATERIAL	FINISH . MARKS				
備考 REMARKS				製 圖 DRAWN	擔 當 DESIGNED	檢 圖 CHECKED	承 認 APPROVED	出 圖 RELEASED	
				H.G PARK	H.G PARK	D.G KIM	H.S KIM	ENG 23.05.18 DEPT	
				19.04.17	19.04.17	19.04.17	19.04.17		
舊製品 CODE NO. (OLD)			圖番 DRAWING NO.		製品名 PART NO.				
			EDC3-632635-80		U.FL-R-SMT-K (800)				
		尺 度 SCALE 10:1	單位 UNITS mm	 HIROSE KOREA CO.,LTD.		製品 CODE NO.			
						CL 6327-0362-5-800			
				1 2					

May.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

[Attention when wiring for U.FL-2LPK-066 harness]




The cable must not touch the case directly in a movable part.








[When the part that winds repeatedly is near the plug]

Please install the guide so that the plug should not come off from the cable according to the winding direction.

Please separate the winding position from the plug edge by 10mm or more.



It is recommended to do to put among the tapes that slip easily and for the load not to hang directly to the cable.




Please avoid the usage to which the cable bends repeatedly in the direction of the cable axis in a movable part.

[PRECAUTIONS FOR HANDLING]

- ◆ Connector insertion and extraction
 - a. Connector shall be extracted vertically by specialised extraction JIG.
Part No:U.FL-LP(V)-N-2
Never hold the cable when extracting the cable because it damages the connector.
 - b. Insert the connector as perpendicularly to the mating surface as possible by aligning the mating axes of both connectors. Do not excessively slant the connectors when inserting.

- ◆ Allowable loads on the cable after the connectors are mated.
The figures below show the maximum allowable loads on the cable. Do not apply loads exceeding these values to the cable.



図番 DRAWING NO. EDC3-632635-80	製品名 PART NO. U.FL-R-SMT-K (800)	2/2
HRS HIROSE KOREA CO.,LTD.	製品 CODE NO. CL 6327-0362-5-800	