





APPLICABLE STANDARD						
RATING	Operating temperature range	-40 °C to 125 °C(note 1)	Storage temperature range	-10 °C to 50 °C (Packed condition)		
	Voltage	50 V AC / DC	Operating or storage humidity range	Relative humidity 90%MAX(Not dewed)		
	Current	0.5 A	Applicable cable (FPC/FFC)	t = 0.3 ± 0.05 mm, Gold plating Heat resistance : 125 °C		
SPECIFICATIONS						
ITEM	TEST METHOD		REQUIREMENTS	QT	AT	
CONSTRUCTION						
General examination	Visually and by measuring instrument.		According to drawing.	×	×	
Marking	Confirmed visually.			×	×	
ELECTRICAL CHARACTERISTICS						
Contact resistance	1 mA (DC or 1000 Hz).		50 mΩ MAX. Including FPC/FFC bulk resistance (L = 8 mm)	×	—	
Insulation resistance	100 V DC.		500 MΩ MIN.	×	—	
Voltage proof	150 V AC for 1 min.		No breakdown.	×	—	
MECHANICAL CHARACTERISTICS						
Mechanical operation	20 times insertions and extractions.		① Contact resistance : 50 mΩ MAX. ② No damage, crack and looseness of parts.	×	—	
Vibration	Frequency 10 to 55 Hz, half amplitude 0.75 mm, for 10 cycles in 3 axial directions.			① No electrical discontinuity of 1 μs. ② Contact resistance : 50 mΩ MAX. ③ No damage, crack and looseness of parts.	×	—
Shock	981 m/s ² , duration of pulse 6 ms at 3 times in 3 both axial directions.				×	—
FPC retention force	Measured by applicable FPC. (Connector, FPC at initial condition. Thickness of FPC shall be t = 0.30 mm)		Direction of insertion : 0.4 × n N MIN. (n : Number of contacts) (note 2)	×	—	
ENVIRONMENTAL CHARACTERISTICS						
Rapid change of temperature	Temperature -55→+15 to +35→+125→+15 to +35 °C Time 30→ 2 to 3 → 30 → 2 to 3 min. Under 1000 cycles.		① Contact resistance : 50 mΩ MAX. ② Insulation resistance : 50 MΩ MIN. ③ No damage, crack and looseness of parts.	×	—	
High temperature and high humidity	Exposed at 60 ± 2 °C, Relative humidity 90 to 95 %, 1000 h.			×	—	
Damp heat, cyclic	Exposed at -10 to +65 °C, Relative humidity 90 to 96 %, 10 cycles, Total 240 h.			×	—	
Dry heat	Exposed at 125 ± 2 °C, 1000 h.		① Contact resistance : 50 mΩ MAX. ② No damage, crack and looseness of parts.	×	—	
Cold	Exposed at -55 ± 3 °C, 1000 h.			×	—	
Sulphur dioxide [JIS C 60068-2-42]	Exposed at 40 ± 2 °C, Relative humidity 80 ± 5 %, 25 ± 5 ppm for 96 h.		Contact resistance : 50 mΩ MAX.	×	—	
	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE	
	1	DIS-F-00022835	GT. TSURUMAKI	HS. HIRAHARA	20250423	
REMARK			APPROVED	SJ. OKAMURA	20200813	
			CHECKED	SJ. OKAMURA	20200813	
			DESIGNED	SG. MASAKI	20200813	
Unless otherwise specified, refer to IEC 60512.			DRAWN	NM. YONEYAMA	20200812	
Note QT:Qualification Test AT:Assurance Test X:Applicable Test			DRAWING NO.		ELG-391183-99-00	
	SPECIFICATION SHEET		PART NO.	FH75-**S-0. 5SH(99)		
	HIROSE ELECTRIC CO., LTD.		CODE NO.	CL0580	 1/2	

Apr.1.2025 Copyright 2025 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
 In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

SPECIFICATIONS

ITEM	TEST METHOD	REQUIREMENTS	QT	AT
Resistance to soldering heat	1) Reflow soldering (To be 2 times MAX.) Peak TMP. 250 °C MAX. Reflow TMP. over 230 °C within 60 sec. Pre-heating. 150 to 200 °C 90 to 120 sec. 2) Soldering irons : 400 ± 10 °C, for 5 ± 1 sec.	No deformation of case of excessive looseness of the terminals. (note 3) 	×	—
Solderability	Soldered at solder temperature, 245 ± 3 °C for immersion duration, 3 ± 0.3 sec.	A new uniform coating of solder shall cover a minimum of 95 % of the surface being immersed.	×	—

(note 1)

The heat resistant temperature when using FFC is 105°C.

When the heat resistant temperature of FPC/FFC is less than 125°C/105°C, the heat resistant temperature of FPC/FFC is applied.


(note 2)

Stabilize the FPC/FFC to PCB or something fixed, if pull-up or pull-down force is expected to be applied to the FPC/FFC.

There's case which FPC/FFC retention force doesn't fulfill the value FPC/FFC specification affects the result of FPC/FFC retention force.

(note 3)

Blisters which may be generated on the housing do not affect product performance.

Note QT:Qualification Test AT:Assurance Test X:Applicable Test		DRAWING NO.		ELC-391183-99-00	
HRS	SPECIFICATION SHEET		PART NO.	FH75-**S-0.5SH(99)	
	HIROSE ELECTRIC CO., LTD.		CODE NO	CL0580	 2/2