APPLI	ICAB	LE STANI	DARD									
RATING	Т	OPERATING TEMPERATURE RANGE		-25 °C TO 60 °	C 2	STORAGE TEMPERAT	URE RAN	IGE	1> -25 °C TO	60 °C	2	
		/OLTAGE	CURENT									
SPECIFICATIONS												
	ITE	М		TEST METHOD				REQU	IREMENTS	QT	AT	
CONS	STRU	JCTION										
GENERAL EXAMINATION			VISUALLY AND BY MEASURING INSTRUMENT.			ACCO	ACCORDING TO DRAWING.			Х	Х	
MARKING			CONFIRMED VISUALLY.							X	X	
-	TNUC	DE	SCRIPTION	ON OF REVISIONS	DESIGNED			CHECKED		DA	DATE	
			DIS-	E-00002227		TS. ITO	1		TU. TANIGUCHI	2019	90418	
REMARK			A TE D. 4 .	TERM IN NOT INC. USES			APPRO		HO. MIWA		50105	
1 PACKING MATERIA				RIAL IS NOT INCLUDED.			CHEC		TH. KAMEYA		50105	
							DESIGNED		SS. SATOH	20050105		
Unless otherwise specified, refer to JIS C 5402.							DRAWN		SS. SATOH	20050105		
Note C	QT:Qualification Test AT:Assurance Test X:Applicable Test						RAWING NO. ELC4-1			34–01		
R	5			CATION SHEET		PART NO.			TM21P-88P (**)		1	
`		HIROSE ELECTRIC CO., LTD.			(CODE NO.					1/1	