	,	vtive equipment / device which demand high reliability, kindly contact our sales window correspondents.
		등
		ğ
		ō
		င္တ
		ĕ
		ō
		S
		≶
		ಠ
	•	⋚
		<u>&gt;</u>
		<u>8</u>
		ğ
		_
24 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.		3
Š	,	ž
ē		ğ
es		፳
Ŷ		ဗ
ts		<u>&gt;</u>
녌		ğ
₹	•	₹
≐		~
₹	:	≌
<u>.</u>	•	ឨ
=	:	<u>@</u>
_		ē
٠.		_
$\mathbf{z}$		₫
		_
₹		2
Ė		ā
$\mathcal{C}$		등
4		ŏ
Ī		듯
ш	•	⋛
ઝ		⋝
$\stackrel{>}{\sim}$		ĕ
	•	₹
_	-	é
Ž		~
2	٠	Ħ
Ħ		ē
b		≒
Ξ	•	≌
ğ		혓
3		an an
4		≥
Ń	•	₫
ĭ		Ĕ
Ċ	,	돧
⋛	•	₹
≌		ō
_		Ë
		S
		≒
	•	⋍
		5
	•	ŧ
		뚰
		ಶ
	•	š
		Ö
		ပ
		Ö
		se
		ğ
		_

	DESCRIPTION	ION OF REVISIO		IONS BY		DATE		COUNT	DESCRIPTION C	F REVISIONS	BY (	CHKD	DATE
							<u></u>				ļ		
$\triangle$	DI E OTAL	5455									<u> </u>	<u> </u>	
APPLICA	BLE STAN	DARD						STOR	RAGE	T			
	TEMPERATUR	RE RANGE	-5	5 °	C T	O 85	°C	TEMP	PERATURE RANGE — °C TO —			°C	
RATING	VOLTAG	E	RAN					RANG				- %	
	CURREN	Т						APPL	ICABLE CABLE	N	/AX	φ <b>9</b> .6	}
					S	PECII	FICA	TION	1S		•		
	EM			TES	T ME	THOD			REQ	UIREMEN	ITS		QT AT
	RUCTION	1, (6) (4) (5)	( A N/D	50/14	- A O L II	DINO INO	FOUNT	<del>.</del>	ACCORDING TO	DDAMNIC			T = T =
GENERAL EXAMINATION VISUALLY AND BY MEASURING INSTR MARKING VISUALLY AND BY MEASURING INSTR													
	NICAL CHA	<u> </u>				· · · · · · · · · · · · · · · · · · ·	ITOME	<u> </u>					1010
VIBRATION		FREQUE	NCY	10 T	O 55				NO DAMAGE, CR	RACK AND LO	OSEN	ESS,	101-
		AMPLITU FOR 3				m/s² A	T 2	h,	OF PARTS.				
вноск		490 m/s <sup>2</sup> l	DIREC	TION	S OF F		1 ms A	Т 3					
ENI/IRO	NMENTAL	CHARA	· · ·		TICS								
	N SALT MIST	EXPOSE	O IN				PRAY F		NO DAMAGE, CR	ACK AND LO	OSEN	ESS,	TOI –
		48	h.		,			](	OF PARTS.				
REMARKS							[	DRAWN	DESIGNED	CHECKED	APPR	OVED	RELEASED
		nified rot	ior to	II e	C 540	<b>17</b>							RELEASED
Jnless otl	nerwise spec						G 191		DESIGNED  Gho				RELEASED
Unless otl	nerwise spec ualification Test HIROSE ELE	AT:Assu	rance O., L	Test .TD.	○: <b>Ap</b>		999 1999 st	.k.b. 1.11, 6 DN SH	199 11, & HEET PART N	Y. Enum 99.11.5	){,¶ 99.1	(Liva)	
Note QT:Q	nerwise spec ualification Test HIROSE ELE	AT:Assu	rance	Test .TD.	O:App	olicable Tes	G /9// st CATIO	.k.b. 1.11, 6 DN SH	199 11, & PART NO DE NO.	Y. Enual 97.11.5	)(,¶ 99.1 6 8 -	(Liva)	