



Check point		Measure (mm)	
Cover location.	C	0.1 to 0.5	
Location of tip of the Core.	D	0.2 to 0.5	
Bell-mouth.	E	0.1 to 0.2	
Bent-up.	F	5°MAX	
Bent-down.	G	5°MAX	
Twist.	H	± 2°MAX	
Rolling.	I	± 5°MAX	
Height of rance.	J	0.20 to 0.25	
Cut-off tab.	K	0.1MAX	
Strip length prior to crimping.	L	$\boxed{2}$ 1.2 to 1.9	
Height of metal cut-out teeth.	M	0.1MAX	
Width.	Wire barrel.	N	0.96MAX
	Insulation barrel.	P	1.02MAX
Gap dimension.	Q	0.12 to 0.25	

NOTE 1 To adjust applicator, please check the crimp condition (crimp height and configuration) by using cable.

$\boxed{2}$  This dimension is for reference. please adjust it to meet specified dimensions after the crimping.

COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE												
$\triangle$																
TITLE		<div style="display: flex; justify-content: space-between; align-items: center;"> <div style="text-align: center;"> <p>DF13-3032SCF(A)(##)</p> <p>Crimp quality standard.</p> </div> <div style="text-align: right;"> <p><b>HRS</b> HIROSE ELECTRIC CO., LTD.</p> <table border="1" style="font-size: small;"> <tr> <td>APPROVED</td> <td>HS. OKAWA</td> <td>20181019</td> </tr> <tr> <td>CHECKED</td> <td>SZ. ONO</td> <td>20181019</td> </tr> <tr> <td>CHARGED</td> <td>HT. SATO</td> <td>20181019</td> </tr> <tr> <td>WRITTEN</td> <td>SK. CHIBA</td> <td>20181019</td> </tr> </table> </div> </div>			APPROVED	HS. OKAWA	20181019	CHECKED	SZ. ONO	20181019	CHARGED	HT. SATO	20181019	WRITTEN	SK. CHIBA	20181019
APPROVED	HS. OKAWA				20181019											
CHECKED	SZ. ONO				20181019											
CHARGED	HT. SATO				20181019											
WRITTEN	SK. CHIBA	20181019														
TECHNICAL SPECIFICATION		ETAD-H0895-00	$\triangle$	1/1												