May.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

Applicable standard					
Rating	Operating Temperature Range	-55 to +105°C (Note1)	Storage Temperature Range		-10 °C to +60°C (Note3)
	Operating Humidity Range	20% to 80% (Note2)	Storage Humidity Range		40% to 70% (Note3)
	Applicable Connector	DF51-4S-2C(##)	Current		AWG 30 : 0.5A AWG 28 : 1.0A AWG 22-26 : 2.0A
	Voltage	250 V AC/DC	UL・C-UL Rating	Voltage	30V AC/DC
				Current	2.0A

Specifications

Item	Test method	Requirements	QT	AT
Construction				
General Examination	Visually and by measuring instrument.	According to drawing.	X	X
Marking	Confirmed visually.		X	X
Electric Characteristics				
Contact Resistance Millivolt Level Method	20mV MAX, 1mA (DC or 1000Hz).	30 mΩ MAX.	X	—
Insulation Resistance	500 V DC.	1000 MΩ MIN.	X	—
Voltage Proof	650 V AC for 1 min.	No flashover or breakdown.	X	—
Mechanical Characteristics				
Mechanical Operation (An Plating)	50 times insertion and extraction.	1.No damage, crack or looseness of parts.	X	—
Mating and unmating Force (Au Plating) △2	It takes out and inserts with a conformity connector.	1.Insertion Force : 21.7N MAX. 2.Extraction Force : 1.0N MIN.	X	—
Vibration	Frequency 10 to 55 Hz, single amplitude 0.75 mm, at 10 cycles for 3 direction.	1.No electrical discontinuity of 1 μs. 2.No damage, crack or looseness of parts.	X	—
Shock	Acceleration 490 m/s^2 duration of pulse 11 ms at 3 times for 3 directions.		X	—
Environmental Characteristics				
Damp Heat (Steady State)	Exposed at 40 ± 2°C , humidity 90 to 95 %, 96 h. (After leaving the room temperature for 1 to 2h.)	1.Insulation resistance: 500 MΩ MIN. 2.No damage, crack or looseness of parts.	X	—
Rapid Change Of Temperature	Temperature -55°C→ +105°C Time 30min→ 30min Under 5 Cycles. (The transferring time of the tank is 2 to 3 MIN) (After leaving the room temperature for 1 to 2h.)	1.Insulation resistance: 1000 MΩ MIN. 2.No damage, crack or looseness of parts.	X	—
Dry Heat	Exposed at 105±2°C, 96h		X	—
Cold	Exposed at -55±3°C, 96h		X	—

Remarks
Note 1: Include the temperature rising by current.
Note 2: No condensing.
Note 3: Apply to the unused and packaged condition.

	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
△2	1	DIS-H-00018757	KT.NUMATA	TT.OHSAKO	20230803

APPROVED	SJ.OKAMURA	20230324
CHECKED	SJ.OKAMURA	20230324
DESIGNED	SN.MIWA	20230324
DRAWN	SN.MIWA	20230324

Unless otherwise specified, refer to IEC 60512.

Note QT:Qualification Test AT:Assurance Test X:Applicable Test

DRAWING NO. ELC-401457-00-00

HRS	SPECIFICATION SHEET	PART NO.	DF51B-4EP-2A	
	HIROSE ELECTRIC CO., LTD.	CODE NO.	CL0543-5135-0-00 △2	1/1

FORM HD0011-2-1