

APPLICABLE STANDARD							
RATING	OPERATING TEMPERATURE RANGE	-55 °C TO 85 °C <sup>(1) (2)</sup>		STORAGE TEMPERATURE RANGE	-10 °C TO 60 °C <sup>(3)</sup>		
	OPERATING HUMIDITY RANGE	RH 85 % MAX <sup>(2) (4)</sup>		STORAGE HUMIDITY RANGE	RH 70 % MAX <sup>(3) (4)</sup>		
	VOLTAGE	60 V AC <sup>(5)</sup>		CURRENT	0.5A <sup>(5)</sup>		
	APPLICABLE CABLE	FFC <sup>(6)</sup>					
SPECIFICATIONS							
ITEM		TEST METHOD		REQUIREMENTS		QT	AT
CONSTRUCTION							
GENERAL EXAMINATION		VISUALLY AND BY MEASURING INSTRUMENT.		ACCORDING TO DRAWING.		×	×
MARKING		CONFIRMED VISUALLY.				×	×
ELECTRIC CHARACTERISTICS							
CONTACT RESISTANCE		20 mV MAX, 1 mA(DC OR 1000Hz)		80 mΩ MAX. <sup>(7)</sup>		×	
INSULATION RESISTANCE		100 V DC.		500 MΩ MIN.		×	
VOLTAGE PROOF		200 V AC FOR 1 min.		NO FLASHOVER OR BREAKDOWN.		×	
MECHANICAL CHARACTERISTICS							
INSERTION AND WITHDRAWAL FORCES		MEASURED BY APPLICABLE CONNECTOR.		INSERTION FORCE: 15.5 N MAX. WITHDRAWAL FORCE: 1.55 N MIN.		×	
MECHANICAL OPERATION		50 TIMES INSERTIONS AND EXTRACTIONS.		① CONTACT RESISTANCE: NO VARIATION OF 20 mΩ OR MORE FROM INITIAL VALUE. ② NO DAMAGE, CRACK AND LOOSENESS OF PARTS.		×	
VIBRATION		FREQUENCY 10 TO 55 Hz, SINGL AMPLITUDE : 0.75 mm, AT 2 h FOR 3 AXIAL DIRECTIONS.		① NO ELECTRICAL DISCONTINUITY OF 1 μs. ② NO DAMAGE, CRACK AND LOOSENESS OF PARTS.		×	
SHOCK		490 m/s <sup>2</sup> , DURATION OF PULSE 11 ms AT 3 TIMES FOR 3 BOTH AXIAL DIRECTIONS.				×	
LOCK STRENGTH		MATE TO APPLICABLE CONNECTOR AND APPLY PULL FORCE HORIZONTALLY.		30 N MIN.		×	
FFC RETENTION FORCE		ASSEMBLE APPLICABLE FFC AND PULL HORIZONTALLY WITH 10mm/min IN MATING DIRECTION.		10 N MIN. <sup>(6)</sup>		×	
ENVIRONMENTAL CHARACTERISTICS							
DAMP HEAT (STEADY STATE)		EXPOSED AT 40±2 °C, 90 ~ 95 %, 96 h.		① CONTACT RESISTANCE: NO VARIATION OF 20 mΩ OR MORE FROM INITIAL VALUE.		×	
DRY HEAT		EXPOSED AT 85±2 °C, 96 h		② INSULATION RESISTANCE: 500 MΩ MIN.			
RAPID CHANGE OF TEMPERATURE		TEMPERATURE -55→+5~+35→+85→+5~+35°C TIME 30→ 5 MAX→ 30→5 MAX min. UNDER 5 CYCLES.		③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS.		×	
CORROSION SALT MIST		EXPOSED IN 5 % SALT WATER SPRAY FOR 48 h.		① CONTACT RESISTANCE: NO VARIATION OF 20 mΩ OR MORE FROM INITIAL VALUE.		×	
SULFUR DIOXIDE		EXPOSED IN 25 PPM FOR 96 h. (TEST STANDARD: JIS C 60068)		② NO DEFECT SUCH AS CORROSION WHICH IMPAIRS THE FUNCTION OF CONNECTOR.		×	
	COUNT	DESCRIPTION OF REVISIONS		DESIGNED	CHECKED	DATE	
△							
REMARKS				APPROVED	HS. OKAWA	12. 11. 27	
(1) INCLUDE TEMPERATURE RISE CAUSED BY CURRENT-CARRYING. (2) OPERATING TEMPERATURE SHOULD BE -55 TO 40°C WHEN HUMIDITY EXCEEDS 80% RH. (3) THE SPECIFICATION IS APPLIED TO THE PRE-ASSEMBLED COMPONENT AND THE CABLE ASSEMBLED PRODUCT BOTH IN DELIVERY AND STORAGE, BEFORE ASSEMBLED TO PCB. (4) THERE MUST NOT BE DEWFALL. (5) IT IS THE MAXIMUM VALUE OF CONNECTOR. CONFIRM THE SPECIFICATION OF THE CABLE. (6) ONLY FFC THAT PROCESSES THE TERMINAL THAT WE SPECIFIED. (7) DON'T INCLUDE CONDUCTOR RESISTANCE OF CABLE.				CHECKED	HT. YAMAGUCHI	12. 11. 27	
				DESIGNED	Y.J. ASAO	12. 11. 27	
				DRAWN	Y.J. ASAO	12. 11. 27	
Unless otherwise specified, refer to JIS-C-5402.							
Note QT:Qualification Test AT:Assurance Test X:Applicable Test				DRAWING NO.		ELC4-344220-01	
HRS	SPECIFICATION SHEET			PART NO.	FX16F-31P-HC		
	HIROSE ELECTRIC CO., LTD.			CODE NO.	CL575-3266-8-00	△	1/1