

Apr.1.2025 Copyright 2025 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

APPLICABLE STANDARD		SD Card Specifications Ver. 1.0		
RATING	OPERATING TEMPERATURE RANGE	-25 °C TO +85 °C (NOTE1)	STORAGE TEMPERATURE RANGE	-40 °C TO +85 °C
	VOLTAGE	AC 125V	OPERATING HUMIDITY RANGE	95%MAX (NON-CONDENSING)
	CURRENT	0.5A		

SPECIFICATIONS

ITEM	TEST METHOD	REQUIREMENTS	QT	AT
------	-------------	--------------	----	----

CONSTRUCTION

GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	X	X
MARKING	CONFIRMED VISUALLY.		X	X

ELECTRIC CHARACTERISTICS

CONTACT RESISTANCE MILLIVOLT LEVEL METHOD IEC60512-2-2a	OPEN VOLTAGE 20 mV AC MAX, TEST CURRENT 1mA.	INITIALLY 100 mΩ MAX (NOTE 2).	X	-
VOLTAGE PROOF IEC60512-2-4a	500 Vrms AC IS APPLIED FOR 1 MINUTE.	① NO FLASHOVER OR BREAKDOWN. ② CURRENT LEAKAGE 1mA MAX.	X	-
INSULATION RESISTANCE IEC60512-2-3a	MEASURE WITHIN 1 MINUTE AFTER APPLYING 500 V DC.	INITIALLY 1000 MΩ MIN.	X	-

MECHANICAL CHARACTERISTICS

CARD INSERTION FORCE	MEASURED BY APPLICABLE CORD AT 25mm/min.	THE INITIAL STAGE:10 N MAX. AFTER MECHANICAL OPERATION:10N MAX.	X	-
MECHANICAL OPERATION [OFFICE ENVIRONMENT] EIA364B class1.1	10000 TIMES INSERTIONS AND WITH DRAWAL SHALL BE MADE AT THE CYCLE RATE 400 TO 600 CYCLES/h.	① CONTACT RESISTANCE: AFTER TEST 40 mΩ MAX CHANGE. (CONTACT RESISTANCE REVERSION BY INSERTION AND EXTRACTION IS AVAILBLE) ② NO MECHANICAL DAMAGE SHALL OCCUR ON THE PARTS.	X	-
VIBRATION AND HIGH FREQUENCY IEC60512-4-6d	FREQUENCY 10 TO 55 TO 10 Hz/min, SINGLE AMPLITUDE 0.75 mm FOR 2 h IN 3 DIRECTIONS.	① NO ELECTRICAL DISCONTINUITY OF 100 ns. ② NO MECHANICAL DAMAGE SHALL OCCUR ON THE PARTS.	X	-
SHOCK IEC60512-4-6c	ACCELERATION 490m/s ² STANDARD HOLDING TIME 11 ms, SEMI-SINE WAVE FOR 3TIMES IN 3 DIRECTIONS.		X	-

ENVIRONMENTAL CHARACTERISTICS

DAMP HEAT, CYCLIC IEC60512-6-11m	10 CYCLES (1 CYCLE=24 HOURS)WITH CONNECTORS ENGAGED.	① CONTACT RESISTANCE: AFTER TEST 40 mΩ MAX CHANGE. ② INSULATION RESISTANCE: AFTER TEST 100 MΩ MIN. ③ NO MECHANICAL DAMAGE OR HEAVY CORROSION SHALL OCCUR ON THE PARTS.	X	-
----------------------------------	--	--	---	---

The graph illustrates a 24-hour damp heat cycle. The y-axis represents both Relative Humidity (%) and Circumference temperature. The x-axis represents time in hours. The cycle includes a 15-minute ramp up to a maximum temperature of +2°C, a dwell at +2°C, a 15-minute ramp down to a maximum temperature of -2°C, a dwell at -2°C, a 15-minute ramp down to +28°C, a dwell at +28°C, and a 15-minute ramp up to +22°C. Humidity levels are specified as 5%, 90%, 96%, and 95% at various points in the cycle.

COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
△				

REMARK NOTE 1:INCLUDE THE TEMPERATURE RISE BY CURRENT. NOTE 2:CONTACT RESISTANCE INCLUDES CONDUCTOR RESISTANCE. UNLESS OTHERWISE SPECIFIED, THE TEST SHOULD BE DONE UNDER TEMP.+15 TO +35°C, AIR PRESSURE 86 TO 106kPa, RELATIVE HUMIDITY 25 TO 85%.	APPROVED	HT. YAMAGUCHI	20200318
	CHECKED	HT. YAMAGUCHI	20200318
	DESIGNED	MT. ITANO	20200318
	DRAWN	DS. HIROWATARI	20200317

Note QT:Qualification Test AT:Assurance Test X:Applicable Test	DRAWING NO.	ELC-153563-92-00
--	-------------	------------------

HRS	SPECIFICATION SHEET	PART NO.	DM1B-DSF-PEJ (92)
	HIROSE ELECTRIC CO., LTD.	CODE NO.	CL609-0003-5-92 △ 1/2

SPECIFICATIONS

ITEM	TEST METHOD	REQUIREMENTS	QT	AT
RAPID CHANGE OF TEMPERATURE IEC60512-6-11d	5 CYCLES (1 CYCLE=1 HOUR)WITH CONNECTORS ENGAGED. TEMPERATURE:-55 to +85°C	① CONTACT RESISTANCE: AFTER TEST 40 mΩ MAX CHANGE. ② INSULATION RESISTANCE: AFTER TEST 100 MΩ MIN. ③ NO MECHANICAL DAMAGE OR HEAVY CORROSION SHALL OCCUR ON THE PARTS. NO MECHANICAL DAMAGE OR HEAVY CORROSION SHALL OCCUR ON THE PARTS.	X	—
DRY HEAT IEC60512-6-11i	EXPOSED AT +85 °C FOR 96 HOURS WITH CONNECTORS ENGAGED.		X	—
COLD IEC60512-6-11j	EXPOSED AT -25 °C FOR 96 HOURS WITH CONNECTORS ENGAGED.		X	—
DAMP HEAT, STEADY STATE IEC60512-6-11c	EXPOSED AT +40 °C,90 TO 95 % RH, 96 HOURS WITH CONNECTORS ENGAGED.		X	—
HYDROGEN SULFIDE JEIDA 38	EXPOSED IN 3 PPM HYDROGEN SULFIDE , APPROX. 80% RH,96 HOURS, WITH CONNECTORS ENGAGED.		X	—
CORROSION SALT MIST (JIS C 5402 7.1)	EXPOSED IN 5±1 % SALT WATER SPRAY , +35±2°C,48 HOURS, WITH CONNECTORS ENGAGED. AFTER THE TEST,THE TEST SAMPLE SHALL BE RINSED WITH WATER AND DRIED AT THE AMBIENT TEMP. FOR 24 HOURS.		X	—

Note QT:Qualification Test AT:Assurance Test X:Applicable Test

DRAWING NO.

ELC-153563-92-00



SPECIFICATION SHEET

PART NO.

DM1B-DSF-PEJ (92)

HIROSE ELECTRIC CO., LTD.

CODE NO

CL609-0003-5-92



2/2