Apr.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.











HRS DRAWING FOR REFERENCE

Note 1 Avoid angled insertion of crimp contact(DF57-****SCF) to maintain performance reliability.

NO.	MATERIAL	FINISH , REMARKS
1	PBT	UL94V-0. NATURAL(WHITE)

UNITS	SCALE		COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
mm	20 : 1	△0					

HIROSE ELECTRIC CO., LTD.

APPROVED	SJ. OKAMURA	20210727
CHECKED	SZ. ONO	20210727
DESIGNED	HK. HAYASHI	20210727
DRAWN	NK. OOSHIMA	20210727

DRAWING NO.	EDC-344725-10-01
PART NO.	DF57AH-5S-1.2C(10)
CODE NO.	CL0666-0110-0-10

△0 1/2

Apr.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

DF57 Series Mating / Unmating Operation Instruction (For DF57 series)

Mating

①By positioning the convexity of the socket sides to the header concavity, align the centers of the socket and the header in pitch direction.



②Slightly press the socket down at cable side to tilted angle.



③Press down at the lever side with stabilizing the cable side to insert. Mating completes.



HRS DRAWING FOR REFERENCE

Unmating

①Hook the lever with finger nail.



②Lift up to the upper direction and friction lock is released.



③Lift up to the upper direction and positive lock is released. Removal completes.



DRAWING NO.	EDC-344725-10-01
PART NO.	DF57AH-5S-1.2C(10)
CODE NO.	CL0666-0110-0-10

△0 2/2