

APPLICABLE STANDARD								
RATING	OPERATING TEMPERATURE RANGE		-35°C TO +85°C (NOTE 1)		STORAGE TEMPERATURE RANGE	-10°C TO +60°C (NOTE 3)		
	OPERATING HUMIDITY RANGE		40% TO 80% (NOTE 2)		STORAGE HUMIDITY RANGE	40% TO 70% (NOTE 3)		
	VOLTAGE		500V AC/DC		APPLICABLE CABLE	UL1007, AWG20—22		
	CURRENT	AWG 20 AWG 22	5A		APPLICABLE CONTACT	DF33A-2022SC (F)		
								
SPECIFICATIONS								
ITEM		TEST METHOD			REQUIREMENTS		QT	AT
CONSTRUCTION								
GENERAL EXAMINATION		VISUALLY AND BY MEASURING INSTRUMENT.			ACCORDING TO DRAWING.		X	X
MARKING		CONFIRMED VISUALLY.					X	X
ELECTRIC CHARACTERISTICS								
INSULATION RESISTANCE		500V DC.			1000MΩ MIN.		X	—
VOLTAGE PROOF		1500V AC FOR 1 min.			NO FLASHOVER OR BREAKDOWN.		X	—
MECHANICAL CHARACTERISTICS								
MECHANICAL OPERATION		30 TIMES INSERTIONS AND EXTRACTIONS.			NO DAMAGE, CRACK OR LOOSENESS OF PARTS.		X	—
VIBRATION		FREQUENCY 10 TO 55 Hz, SINGLE AMPLITUDE 0.75 mm, AT 10 CYCLE FOR EACH, FOR 3 DIRECTIONS.			NO DAMAGE, CRACK OR LOOSENESS OF PARTS.		X	—
SHOCK		490 m/s <sup>2</sup> DURATION OF PULSE 11 ms AT 3 TIMES FOR 3 DIRECTIONS.					X	—
ENVIRONMENTAL CHARACTERISTICS								
DAMP HEAT (STEADY STATE)		EXPOSED AT 40 ± 2 °C, 90 TO 95 %, 96 h.			① INSULATION RESISTANCE: 500MΩ MIN. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.		X	—
RAPID CHANGE OF TEMPERATURE		TEMPERATURE -55→+85°C TIME 30→ 30min. UNDER 5 CYCLES. THE TRANSFERRING TIME OF THE TANK IS 2~3 min.			① INSULATION RESISTANCE: 1000MΩ MIN. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.		X	—
REMARKS NOTE 1:INCLUDING THE TEMPERATURE RISE BY CURRENT. NOTE 2:NO CONDENSING NOTE3:APPLY TO THE CONDITION OF LONGTERM STORAGE FOR UNUSED PRODUCTS BEFORE PCB ON BOARD, AFTER PCB BOARD, OPERATING TEMPERATURE AND HUMIDITY RANGE IS APPLIED FOR INTERIM STORAGE DURING TRANSPORTATION.								
	COUNT	DESCRIPTION OF REVISIONS		DESIGNED		CHECKED	DATE	
	1	DIS-H-007821		HT. SATO		TS. KUMAZAWA	13. 04. 25	
Unless otherwise specifid , refer to JIS C 5402.						APPROVED	HK. UMEHARA	12. 07. 21
						CHECKED	HK. UMEHARA	12. 07. 21
						DESIGNED	HT. SATO	12. 07. 21
						DRAWN	MI. SAKIMURA	12. 07. 21
Note QT:Qualification Test AT:Assurance Test X:Applicable Test				DRAWING NO.		ELC4-338426-00		
	SPECIFICATION SHEET			PART NO.		DF33C-3S-3. 3C		
	HIROSE ELECTRIC CO., LTD.			CODE NO.		CL676-1137-9-00  1/1		