






Applicable standard					
Rating	Operating temperature range 	-55 °C to +105°C (Note1)		Storage temperature range	-10 °C to +60°C (Note3)
	Operating humidity range	20% to 80% (Note2)		Storage humidity range	40% to 70% (Note3)
	Applicable connector	DF63#-*EP-3.96C		Voltage	AC/DC 630V
	Applicable cable	UL1015 AWG 16 to 18 UL1007 AWG 16 to 18		Current	AWG 16 : 15A AWG 18 : 13A
	Insulation diameter	φ2.1 to φ3.2mm			
		Rated Voltage	Rated Current	Overvoltage Category	IP-Degree
UL,C-UL		600V AC/DC	See above	-	-
TÜV		300V AC/DC	See above	-	IP00
Specifications					
Item		Test method		Requirements	QT AT
Construction					
General examination		Visually and by measuring instrument.		According to drawing.	X X
Marking		Confirmed visually.			X X
Electric characteristics					
Contact resistance		20mV MAX, 1mA (DC or 1000Hz).		10 mΩ MAX.	X -
Mechanical characteristics					
Mechanical operation		30 times insertion and extraction.		①Contact resistance: 20 mΩ MAX. ②No damage, crack or looseness of parts.	X -
Vibration		Frequency 10 to 55 Hz, single amplitude 0.75 mm, at 10 cycles for 3 direction.		①No electrical discontinuity of 1 μs. ②No damage, crack or looseness of parts.	X -
Shock		490 m/s ² duration of pulse 11 ms at 3 times each for 3 both axial directions.		①No electrical discontinuity of 1 μs. ②No damage, crack or looseness of parts.	X -
Environmental characteristics					
Damp heat (Steady state)		Exposed at 40 ± 2°C , 90 to 95 %, 96 h. (After leaving the room temperature for 1-2h.)		①Contact resistance: 20 mΩ MAX. ②No damage, crack or looseness of parts.	X -
Rapid change of temperature		Temperature -55°C → +85°C Time 30min → 30min Under 5 cycles. (The transferring time of the tank is 2-3 min) (After leaving the room temperature for 1-2h.)		①Contact resistance: 20 mΩ MAX. ②No damage, crack or looseness of parts.	X -
<p>Note 1: Include the temperature rising by current.</p> <p>Note 2: No condensing</p> <p>Note 3: Apply to the condition of long term storage for unused products before PCB on board. After PCB on board, operating temperature and humidity range is applied for interim storage during transportation.</p>					
	Count	Description of revisions	Designed	Checked	Date
	1	DIS-H-00002332	MI. SAKIMURA	TS. FUKUSHIMA	16. 11. 29
Remarks				Approved	15. 10. 29
				Checked	15. 10. 29
				Designed	15. 10. 29
				Drawn	15. 10. 28
Unless otherwise specified, refer to IEC 60512.					
Note QT:Qualification Test AT:Assurance Test X:Applicable Test			Drawing No.		ELC-361982-00-00
	Specification sheet		Part No.	DF63-1618PC	
	HIROSE ELECTRIC CO., LTD.		Code No.	CL680-0536-8-00	 1/1