


Mar.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
本製品を車載用途などの高い信頼性が求められる機器にご使用の場合は、弊社までお問合せ下さい。

ELV, RoHS適合品






B-B
(10 : 1)



潰し前展開長
3.6±0.02

A-A
(10 : 1)




潰し前展開長
4.7±0.02


注記１.
適用リテーナー
トヨタ品番:G92SD-42230及びG92SD-42240　②　ヒロセ品番:ZH05M-20DP-R CODE NO:CL756-2211-0-00
適用オスハウジング(A)
トヨタ品番:G92SD-42230　①　ヒロセ品番:ZH05M-17DP-HU(A) CODE NO:CL756-2209-0-00
適用オスハウジング(B)
トヨタ品番:G92SD-42240　①　ヒロセ品番:ZH05M-17DP-HU(B) CODE NO:CL756-2210-0-00
２. 梱包品の取り扱いについては、ATAD-T0946-00「圧着端子リール梱包品取扱説明書」を
△2 ご参照ください。

HRS DRAWING FOR REFERENCE

1.梱包仕様
リール詳細寸法(FREE)



(1)入り数は：15000pcs/リール
(2)総入り数：5リール/箱(合計75000pcs)



NO.	MATERIAL	FINISH , REMARKS
1	黄銅	接点部：Snめっき1.0μm min
		バレル部:Snめっき1.0μm min

TOLERANCES SEE TABLE FOR SPECIFIED, UNLESS OTHERWISE	
OVER TO	TOLERANCE
6	±0.3
6 18	±0.5
18 50	±0.7
50 125	±1

UNITS mm
SCALE 5:1
ANGULAR ±1°
HIROSE ELECTRIC CO., LTD.

ASSEMBLY DRAWING

	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
△2	1	DIS-T-00014052			

APPROVED :	HK. UMEHARA	2022. 02. 25	DRAWING No. ADC-386851-00-03
CHECKED :	OM. MIYAMOTO	2022. 02. 25	PART No. ZH05-2224PCF
DESIGNED :	KO. NAKAMURA	2022. 02. 25	
DRAWN :	KO. NAKAMURA	2022. 02. 25	CODE No. CL0756-2001-0-00 △2 1/1

FORM HC0011-4

3D Model File Name:ADC-386851-00-03