

May.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.  
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

	COUNT	DESCRIPTION OF REVISIONS	BY	CHECKED	DATE		COUNT	DESCRIPTION OF REVISIONS	BY	CHECKED	DATE
△						△					
△						△					
APPLICABLE STANDARD											
RATING	ELECTRIC SOURCE	PHASE	AC・DC	V	Hz	WEIGHT		5kg			
	DISSIPATION POWER					APPLICABLE CONNECTOR		DF13-2630SCF CL 536-0300-5 DF13-2630SCFA CL 536-0298-5			
	AIR SOURCE					APPLICABLE CABLE					
	AIR CONSUMPTION					APPLICABLE EQUIPMENT		CM-105C CL 901-0001-0			
	OPERATING TEMPERATURE LIMIT	℃~℃									
SPECIFICATIONS											
	ITEM	TEST METHOD				REQUIREMENTS		QT	AT		
CONSTITUTION	APPEARANCE, STRUCTURE AND FINISH	Visually and by measuring instrument.				According to drawing.		○	○		
	MARKING	Confirmed visually.				According to drawing.		○	○		
REMARKS						DRAWN	DESIGNED	CHECKED	APPROVED	RELEASED	
						18.10.19 H.KUDO	18.10.19 H.YANAGISAWA	18.10.19 H.TOKUTA	18.10.19 T.ITO		
Unless otherwise specified, refer to											
Note QT:Qualification Test AT:Assurance Test X:Applicable Test											
TO		HIROSE ELECTRIC CO.,LTD.				SPECIFICATION SHEET		PART NO. AP105-DF13-2630S			
PE		CODE NO. (OLD)		DRAWING NO. ELC- 075307-00-00		CODE NO. CL 901-4531-9		1		1	