

APPLICABLE STANDARD					
RATING	OPERATING TEMPERATURE RANGE	-30°C TO +80°C	STORAGE TEMPERATURE RANGE	-40°C TO +85°C	
	OPERATING HUMIDITY RANGE	5% TO 95% RH	APPLICABLE CABLE	OUTER DIAMETER : ϕ 6.8	
SPECIFICATIONS					
ITEM		TEST METHOD		REQUIREMENTS	QT AT
CONSTRUCTION					
GENERAL EXAMINATION		VISUALLY AND BY MEASURING INSTRUMENT.		ACCORDING TO DRAWING.	X X
MARKING		CONFIRMED VISUALLY.			
	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
A					
REMARK			APPROVED	A0. SUZUKI	07.01.25
			CHECKED	NF. MIYAZAKI	07.01.25
			DESIGNED	KI. NAGANUMA	07.01.24
			DRAWN	KI. NAGANUMA	07.01.24
Unless otherwise specified, refer to JIS C 5402.					
Note QT:Qualification Test AT:Assurance Test X:Applicable Test			DRAWING NO.		ELC4-126206-00
HRS	SPECIFICATION SHEET		PART NO.	ST40X-CM1 (6.8)	
	HIROSE ELECTRIC CO., LTD.		CODE NO.	CL241-0063-2-00	⚠ 1/1