May.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

HRS DRAWING FOR REFERENCE



RECOMMENDED PATTERN



4 DRAWING FOR PACKING (FREE)











1 INTERFACE DIMENSIONS CONFORMS TO USB2.0 SPECIFICATION.
2 CO-PLANARITY TO BE 0.08MAX.
3 PLATING
CONATACT AREA:GOLD 0.05μm MIN OVER PALLADIUM NICKEL 0.75μm MIN.
LEAD AREA :GOLD 0.05μm MIN.
UNDER PLATING:NICKEL 2μm MIN.
4 PER REEL:2000pcs.
5 AS FOR PART No.3. THE PERFORMANCE REMAINS GOOD EVEN IF THERE IS A RUBBING WOUND BY THE ASSEMBLY PROCESS.
6 AS FOR PART No.2. A PART OF SHAPE MAY BECOME DIFFERENT DEPENDING ON THE PRODUCTION METHOD.

NO.	MATERIAL	FINISH , REMARKS	NO.	MATERIAL	FINISH , REMARKS
2	LCP	COLOR BLACK UL94V-0	5	PE	
1	COPPER ALLOY	3	4	PS	
			3	STAINLESS STEEL	TIN PLATING 1μm min. LUBRICANT

UNITS	SCALE		COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
mm	5 : 1	0					

HIROSE ELECTRIC CO., LTD.

APPROVED	NM. NISHIMATSU	15. 10. 27	DRAWING NO. EDC-126514-31-00
CHECKED	KN. ICHIKAWA	15. 10. 27	PART NO. ZX62MD1-B-5P(31)
DESIGNED	TS. ITO	15. 10. 27	CODE NO. CL242-0041-6-31
DRAWN	AK. AKIYAMA	15. 10. 27	0 1/1