APPLICABLE STANDARD										
	OPERATING TEMPERATUR	−25°C TO +8	5°C	STORAGE TEMPERATURE RANGE			−25°C TO +60°C			
RATING	OPERATING&STORAGE HUMIDTY RANGE		85%MAX		APPLI	APPLICABLE CABLE		CABLE DIAMETER :	φ5.1 ~	- 7.1
	VOLTAGE				CURRENT					
					N.					
SPECIFICATIONS										
IT	EM		TEST METHOD				REQUIREMENTS QT			
CONSTR	UCTION									
GENERAL EXAMINATION		VISUALLY AND BY MEASURING INSTRUMENT.				ACCORDING TO DRAWING.				X
MARKING		CONFIRMED VISUALLY.							Х	Χ
COUN	Γ DE	SCRIPTION OF R	REVISIONS		IED	CHECKED		DA	DATE	
2 1		216	KN. ICH			1	TU. TANIGUCHI		1019	
REMARK THIS PRODUCT SHALL BE MATED WITH DH40-17						APPRO		KN. ICHIKAWA	20100705	
			LIES TO DH40-17S OR			CHECK		KN. ICHIKAWA	20100705	
			IECHANICAL, RACTERISTICS.			DESIGN	NED	TU. TANIGUCHI	20100705	
		specified, refer				DRAWN		TU. TANIGUCHI	J. TANIGUCHI 20100	
Note QT:Q	ualification Tes	st AT:Assurance	Test X:Applicable T	est X:Applicable Test DF				ELC-126590-00-00		
SPECIFICATION SHEET					PART N	10.	DH-17-CV2B			
11.	HIROSE ELECTRIC CO., LT				CODE	NO. CL	CL244-0013-3-00			1/1