

COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE
△					△				
△					△				
APPLICABLE STANDARD									
RATING	OPERATING TEMPERATURE RANGE	-40 °C ~ +70 °C			STORAGE TEMPERATURE RANGE	-50 °C ~ +85 °C			
	VOLTAGE	50 V AC or DC			OPERATING HUMIDITY RANGE	85%RH MAX			
	CURRENT	0.5A (1A ACCEPTABLE FOR ANY 2 CONTACTS)			APPLICABLE CABLE	JACKET DIAMETER : φ4.5MAX INSULATION : φ0.6MAX (AWG30)			
SPECIFICATIONS									
ITEM		TEST METHOD			REQUIREMENTS			QT	AT
CONSTRUCTION									
GENERAL EXAMINATION		VISUALLY AND BY MEASURING INSTRUMENT			ACCORDING TO DRAWING			○	○
MARKING		CONFIRMED VISUALLY						○	○
ELECTRIC CHARACTERISTICS									
CONTACT RESISTANCE		100 mA (DC OR 1000 Hz)			70 mΩ MAX			○	—
INSULATION RESISTANCE		100 V DC			1000 MΩ MIN			○	—
VOLTAGE PROOF		250 V AC FOR 1 min			NO FLASHOVER OR BREAKDOWN			○	○
MECHANICAL CHARACTERISTICS									
INSERTION AND WITHDRAWAL FORCES		MEASURED BY APPLICABLE CONNECTOR.			INSERTION FORCE: 4~10 N (INITIAL) EXTRACTION FORCE: 4~10 N (INITIAL)			○	—
MECHANICAL OPERATION		5000 TIMES INSERTIONS AND EXTRACTIONS.			① AMOUNT OF CHANGE OF CONTACT RESISTANCE: 20 mΩ MAX. ② NO DAMAGE, CRACK AND LOOSENESS, OF PARTS.			○	—
VIBRATION		FREQUENCY 10 TO 55 Hz, SINGLE AMPLITUDE 0.75 mm, OR 98 m/s ² AT 2 h, FOR 3 DIRECTIONS.			① AMOUNT OF CHANGE OF CONTACT RESISTANCE: 20 mΩ MAX. ② NO ELECTRICAL DISCONTINUITY OF			○	—
SHOCK		490 m/s ² DURATION OF PULSE 11 ms AT 3 TIMES FOR 3 DIRECTIONS.			② NO ELECTRICAL DISCONTINUITY OF 1 μs. ③ NO DAMAGE, CRACK AND LOOSENESS, OF PARTS.			○	—
ENVIRONMENTAL CHARACTERISTICS									
RAPID CHANGE OF TEMPERATURE		TEMPERATURE -55 →15~35→85→15~35 °C TIME 30 → 2~3 →30 → 2~3 min UNDER 10 CYCLES.			① AMOUNT OF CHANGE OF CONTACT RESISTANCE: 20 mΩ MAX. ② INSULATION RESISTANCE: 10MΩ MIN. ③ NO FLASHOVER OR BREAKDOWN ④ NO DAMAGE, CRACK AND LOOSENESS, OF PARTS.			○	—
DAMP HEAT (STEADY STATE)		EXPOSED AT +40 °C, 90~95 %, 96 h.						○	—
DRY HEAT		EXPOSED AT +85 °C, 96 h.						○	—
COLD		EXPOSED AT -40 °C, 96 h.						○	—
CORROSION SALT MIST		EXPOSED IN 5 % SALT WATER, 35°C, FOR 48h.			NO HEAVY CORROSION.			○	—
OTHER CHARACTERISTICS									
SOLDERABILITY		SOLERRING POINT OF CONTACTS IMMERSION IN SOLDER BATH OF 245±3°C, 2~3 sec.			MIN. 90% OF SOLDER IMMERSED AREA SHALL BE COVERED NEW SOLDER COATING.			○	—
RESISTANCE TO SOLDERING HEAT		SOLDERING IRON TEMPERATURE: 350±10°C FOR 5±1s			NO DAMAGE, CRACK AND LOOSENESS, OF PARTS.			○	—
REMARKS					DRAWN	DESIGNED	CHECKED	APPROVED	RELEASED
Unless otherwise specified, refer to JIS C 5402.					S. Shimizu '05.7.7	S. Shimizu '05.7.7	Shimizu 05.7.8	Shimizu 05.7.8	
Note QT:Qualification Test AT:Assurance Test O:Applicable Test									
HS HIROSE ELECTRIC CO., LTD.					SPECIFICATION SHEET				
CODE NO.(OLD)					PART NO.				
CL					LX40-16P				
DRAWING NO.		CODE NO.							
ELC4-124883		CL245-0002-3			1/1				