Feb.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

HRS DRAWING FOR REFERENCE



NOTE 1 Do not apply any excessive stress to the cable assembly position.

2 'L' at the end of the Part No. indicates the cable length.
And '*' of the Part No. indicates the cable color.

Length L (mm)	Typical (mm)
50 ≦ L ≦ 200	±4
200 < L ≦ 500	±8
500 < L ≦ 1000	±12
1000 < L	±1.5%

Part No.	Cable color
~068N1T~	Gray
~068N2T~	Black
~068N3T~	White

3. Connector rotation angle is within ±45 degree from the above image.
For long length in the case of
L≧500, the angle is optional.

4. Specifications are subject to
change without notice.

【DIMENSIONS OF CONNECTOR】



【PRECAUTIONS FOR HANDLING】

◆Connector insertion and extraction
a. Connector shall be extracted vertically by specialised extraction JIG.
Part No.:U.FL-LP-N-2CCL Code:CL331-0494-5)
Never hold the cable when extracting the cable because it damages the connector.
b. Insert the connector as perpendicularly to the mating surface as possible by aligning the mating axes of both connectors. Do not excessively slant the connectors when inserting.

◆Allowable loads on the cable after the connectors are mated.
The figures below shot the maximum allowable loads on the cable. Do not apply loads exceeding these values to the cable.



NO.	PART NO.	CODE NO.	NO.	PART NO.	MANUFACTURER
2	U.FL-LP-068HF	CL331-0566-4-00			
1	HRM-200-066PJ2BN(40)	CL323-0788-1-40	3	RF-MF50161	NISSEI ELECTRIC CO.,LTD.

UNITS	SCALE		COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
mm	FREE	0					

HIROSE ELECTRIC CO.,LTD.	APPROVED : TO. KATAYAMA	20190116	DRAWING NO. EDC-385357-00-00
	CHECKED : TO. KATAYAMA	20190116	PART NO. HPJ2-UFLHF6-068N*T-ALRS
	DESIGNED : NK. OOSAWA	20190116	CODE NO. 0 1/1
	DRAWN : NK. OOSAWA	20190116	

FORM HC0011-5-51