

May.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

REV	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE	REV	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE	
△1	1	REVISED	HJ.KIM	HJ.LEE	17.10.13	△						
△						△						
APPLICABLE STANDARD			USB Type-C Cable and Connector Specification Release 1.2 USB Type-C Connector and Cable Assemblies Compliance Document Revision 1.0									
RATING		CURRENT	-									
		VOLTAGE	-									
OPERATING CONDITION			-30℃ ~ +85℃ (INCLUDING TEMP. RISE), 95% RH MAX. (NON-CONDENSING)									
STORAGE CONDITION			-10℃ ~ +60℃ (WITH PACKING), 15% ~ 70% RH									
APPLICABLE CABLE			OUTER DIAMETER OF CABLE Ø 4.8									
Test Description			Test Procedure				Test Requirement				QT	AT
GENERAL EXAMINATION			VISUALLY AND BY MEASURING INSTRUMENT.				ACCORDING TO DRAWING.				○	○
REMARKS					DRAFT	DESIGN	CHECK	APPROVAL	RELEASE			
HIROSE will not guarantee the performance on these specifications in case this product will be mated with the others which is not HIROSE's △1					JS.PARK 16.12.07	JS.PARK 16.12.07	HJ.LEE 16.12.07	TS.KANG 16.12.07	<div>DEPT 17.10.13 ENG</div>			
NOTE) QT : QUALIFICATION TEST, AT : ASSURANCE TEST												
DWG NO			CL NO				PART NO					
ELC4-632262			CL 6240-0007-5				CX60-SLDA					
HRS HIROSE KOREA.CO.,LTD						PRODUCT SPECIFICATION					1 1	