

File E52653  
SR# SR7396334-T001

March 03, 1987

REPORT

On

CONNECTORS FOR USE IN DATA, SIGNAL, CONTROL AND POWER  
APPLICATIONS

Hirose Electric Co Ltd  
Yokohama 222-8566 JAPAN

Copyright © 1987 Underwriters Laboratories Inc.

Underwriters Laboratories Inc. authorizes the above named company to reproduce this Report either in its entirety or the portion of this Report consisting of the Cover Page up to (but not including) the Construction Details Descriptive pages.

D E S C R I P T I O NPRODUCT COVERED:

Connectors Series PCN10 may be followed by additional numbers and letters. Except PCN10M - may be followed by additional numbers and letters. Except for letter "M".

ELECTRICAL RATING:

2 amps maximum, voltage not specified.

**Disconnecting Use - See Sec. Gen. For required markings.**

ENGINEERING CONSIDERATIONS (NOT FOR FIELD REPRESENTATIVE USE):

Conditions of Acceptability - These components are intended for use where the acceptability of the combination has been determined by Underwriters Laboratories.

Use - The following should be determined in judging the acceptability of the combination.

1. These devices are intended for use within the enclosure of an appliance where they will be provided with mechanical protection.
2. The placement of these devices within the equipment enclosure should be such that spacings between the live parts and the equipment are suitable for the particular application.
3. A Contact Security Test has not been done on these devices. The suitability of the pin securement should be evaluated in the end-use product.