





Jun.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.




POLARIZATION MARK




LOT No.

APPLICATION DIAGRAM




RECOMMENDED PATTERN(5:1)
(RECOMMENDED BOARD THICKNESS t=1.6mm)



NOTES 1 :IMMERSION DEPTH INTO POTTING SOLUTION:6.5mm

1	PBT	WHITE, UL94V-0	3	HIPS	TRAY
			2	BRASS	SURFACE:TIN PLATED 1μm min UNDER PLATING:NICKEL PLATED 0.5μm min
NO.	MATERIAL	FINISH , REMARKS	NO.	MATERIAL	FINISH , REMARKS
UNITS mm		SCALE 2 : 1	COUNT 	DESCRIPTION OF REVISIONS	
HIROSE ELECTRIC CO., LTD.		APPROVED : KI. AKIYAMA	12.07.26	DRAWING NO.	EDC3-338387-01
		CHECKED : HK. UMEHARA	12.07.26	PART NO.	DF33C-4DP-3.3DSA(24)
		DESIGNED : HT. SATO	12.07.26	CODE NO.	CL676-1113-0-24
		DRAWN : MI. SAKIMURA	12.07.26		

Jun.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.



NOTES 2 :MINIMUM UNIT OF PURCHASE SHALL BE THE QUANTITY OF CONNECTORS IN TRAY.(135 PIECES)

HRS	DRAWING NO.	EDC3-338387-01	
	PART NO.	DF33C-4DP-3.3DSA(24)	
	CODE NO.	CL676-1113-0-24	△2/2