









May.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.



Recommended pattern(FREE)
(Recommended board thickness t=1.6mm)



- Note 1. Per pack : 100 pieces.
2. The dimension in parenthesis are for reference.
3. UL<File No. E52653>
C-UL<File No. E52653>
TUV<Certificate No. R50318850> authorization article.



1	PBT	UL94V-0<BLACK>	2	Brass	Tin plating 1μm MIN
NO.	MATERIAL	FINISH . REMARKS	NO.	MATERIAL	FINISH . REMARKS
UNITS mm		SCALE 2 : 1	COUNT 	DESCRIPTION OF REVISIONS	DESIGNED
HIROSE ELECTRIC CO., LTD.		APPROVED : KI. AKIYAMA	15.11.11	DRAWING NO.	EDC-364338-00-00
		CHECKED : TS. FUKUSHIMA	15.11.11	PART NO.	DF63-4P-3.96DS
		DESIGNED : YK. YAMAGUCHI	15.11.11	CODE NO.	CL680-0545-0-00
		DRAWN : YK. YAMAGUCHI	15.11.11		