Apr.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.



CONTACT ARRANGEMENTS
VIEWED FROM THE MATING SIDE

NOTES 1 THE RECOMMENDED CLAMP TORQUE, REF.NO.④AND⑩ : 1.5 N·m.
1 THREAD LOCKER TO THE THREADED PORTION OF REF.NO.①
APPLIES TO PREVENT REF.NO. ④ FROM LOOSING.
RECOMMENDED THREAD LOCKER:LOCTITE 263, HENKEL JAPAN LTD.
REF.NO. ⑩ SHALL BE TIGHTENED BY TORQUE AFTER
CLAMPED UNTIL IT TOUCHES THE SURFACE B.
2 ONE EXAMPLE OF THE ROTATION OF REF.NO. ①, ④AND ⑩ ARE SHOWN.
1 3 THE ASSEMBLY THIS PRODUCT APPLIES TO THE MANUAL ETAD-C0355-00.

NO.	MATERIAL	FINISH , REMARKS	NO.	MATERIAL	FINISH , REMARKS
5	POLYAMIDE				
4	BRASS	MATTE FINISH NICKEL PLATED	10	BRASS	MATTE FINISH NICKEL PLATED
3	BERYLLIUM COPPER	GOLD PLATING 0.2μm min. NICKEL UNDER PLATING 2μm min.	9	POLYAMIDE	
			8	BRASS	MATTE FINISH NICKEL PLATED
2	POLYAMIDE	(BLUE)	7	STEEL	NICKEL PLATING
1	ZINC ALLOY	MATTE FINISH NICKEL PLATED	6	STAINLESS STEEL	

UNITS	SCALE		COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
mm	2 : 1	1	2	DIS-C-00016940	HT.ZENBA	EJ.KUNII	20240214

HIROSE ELECTRIC CO., LTD.

APPROVED	MO.SATOH	20051024
CHECKED	EJ.KUNII	20051021
DESIGNED	DS.MATSUNE	20051019
DRAWN	DS.MATSUNE	20051019

DRAWING NO.	EDC4-007759-73
PART NO.	HR10-7P-6S(73)
CODE NO.	CL0110-0024-4-73

1 1/1

FORM HC0011-5-51

HRS DRAWING FOR REFERENCE