

1 2 3 4

推奨パネル取付寸法
パネル厚：2.7以下

The drawing shows a terminal block with a square base and a circular top. The base has four mounting holes, each with a diameter of 2.8 ± 0.2 mm. The top has a circular opening with a diameter of 14.4 ± 0.05 mm. The overall width and height are 25 ± 0.7 mm and 20 ± 0.05 mm, respectively. The drawing includes a cross-section A-A showing the internal structure and a detail of the mounting holes. The drawing is labeled with dimensions and tolerances in millimeters.

25 ± 0.7

2 × Ø 2.8 ± 0.2 (穴)
(部番①)

3.1 ^{+0.05}/₀

45° ± 30'

2 × Ø 2.8 ^{+0.2}/₀

7.5 ^{+0.05}/₀

Ø 14.4 ^{+0.05}/₀

20 ± 0.05

2 × (R 2.5)

Ø 19 ± 0.7

A

Ø 14.3 ^{+0.1}/_{-0.2}

A-A

1

2 圧入

18.1 ± 0.5

10 ± 0.5

3.2 ± 0.7

□ 9.7 ^{+0.1}/_{-0.2}

2 × M2.6 × 0.45
(部番②)

13

13

注 1 適合圧着端子：RP13-PC-222(CL113-0141-7)
適合電線：AWG #24 ~ AWG #28
2 適合圧着端子引抜工具
RP13-PC-TP(CL150-0021-5)

1	ポリカーボネート樹脂	(クロ) UL94V-0	2	鋼	ニッケルめっき		
NO.	MATERIAL	FINISH . REMARKS	NO.	MATERIAL	FINISH . REMARKS		
UNITS mm		SCALE 2 : 1	COUNT 	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
APPROVED : YH. YAMADA		17. 11. 07	DRAWING NO. ADC-010081-71-71				
CHECKED : HY. KOBAYASHI		17. 11. 06	PART NO. RP13A-12RA-15PC(71)				
DESIGNED : DS. MATSUNE		17. 11. 06	CODE NO. CL113-0207-3-71				
DRAWN : DS. MATSUNE		17. 11. 06					

FORM HC0011-5-51

2 3 4

1