



Mar.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.


	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE		COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE
1	1	DIS-C-000585	T.K	E.K	07.07.27						. .
					. .						. .
					. .						. .













PANEL MOUNTED CONDITION





NOTES 1 THE RECOMMENDED TIGHTENING TORQUE OF REF. No.⑧ TO BE 1.5 N·m.
COATING WITH LOCTITE 242 MANUFACTURED BY HENKEL JAPAN OR EQUIVALENT IS RECOMMENDED TO PREVENT LOOSENESS.
2 CONTACT AREA : GOLD 0.2μm min.
DIP AREA: GOLD FLASH.
UNDER PLATING: NICKEL 2μm min.

NO.	MATERIAL	FINISH, REMARKS	NO.	MATERIAL	FINISH, REMARKS
4	PHOSPHOR BRONZE	2	8	BRASS 1	NICKEL PLATING
3	PHOSPHOR BRONZE	2	7	PHOSPHOR BRONZE	NICKEL PLATING
2	POLYPHENYLENE SULFIDE	(BLACK) UL94V-0	6	ETHYLENE PROPYLENE RUBBER	(BLACK)
1	ZINC ALLOY	MATTE FINISH NICKEL PLATING	5	PHOSPHOR BRONZE	2

CODE NO.(OLD)	DRAWN	DESIGNED	CHECKED	APPROVED	RELEASED
CL	M.SATO '07 06 05	H.KAWASHIMA '07 06 05	Y.YAMADA '07 06 20	E.KUNII '07 06 22	. .

SCALE	DRAWING NO.	PART NO.
5 : 1	EDC3-110029-71	HR25-9TR-16SA(71)
UNITS mm	HRS HIROSE ELECTRIC CO., LTD	CODE NO. CL125-0121-0-71 1/1

TO
R

HRS DRAWING FOR REFERENCE

FORM NO.229