



Feb.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE		COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE
1	1	DIS-C-000585	T.K	E.K	07.07.27						. .
					. .						. .
					. .						. .












RECOMMENDED PC BOARD PATTERN
FROM MATING SIDE(4:1)



PANEL CUTOUT
FROM MATING FACE(4:1)
PANEL THICKNESS: 0.7 TO 2

PANEL MOUNTED CONDITION(4 : 1)





HRS DRAWING FOR REFERENCE

NOTES 1 THE RECOMMENDED TIGHTENING TORQUE OF REF. No.⑥ TO BE 1 N·m.
COATING WITH LOCTITE 242 MANUFACTURED BY HENKEL JAPAN OR EQUIVALENT IS RECOMMENDED TO PREVENT LOOSENESS.
2 OVER PLATING : GOLD 0.2μm min.
UNDER PLATING : NICKEL 2μm min.

NO.	MATERIAL	FINISH, REMARKS	NO.	MATERIAL	FINISH, REMARKS
3	PHOSPHOR BRONZE	2	6	BRASS 1	NICKEL PLATING
2	POLYPHENYLENE SULFIDE	(BLACK) 94V-0	5	PHOSPHOR BRONZE	NICKEL PLATING
1	ZINC ALLOY	MATTE FINISH NICKEL PLATING	4	BERYLLIUM COPPER	NICKEL PLATING

CODE NO.(OLD)	DRAWN	DESIGNED	CHECKED	APPROVED	RELEASED
CL	M.SATO '06 09 26	Y.YAMADA '06 09 27	. .	M.SATO '06 09 27	. .

SCALE	DRAWING NO.	PART NO.
5 : 1	EDC3-115089	HR25A-7R-4PA
UNITS: mm	HRS HIROSE ELECTRIC CO., LTD	CODE NO. CL125-0647-6-00 1/1

TO
R

FORM NO.229