

Mar.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.



HRS DRAWING FOR REFERENCE

Notes 1 Total length becomes 37.3±1 when Ref.No.⑥ is screwed into Ref.No.① completery.
2 Applicable crimping contact : HR30-PC-211
(Applicable wire : AWG #26~#30 wire jacket diameter : φ1 max)
applicable crimp contact extraction tool : HR30-TP
△2 3 The recommended clump torque of Ref.No.⑥ to be 0.45~0.5N・m.
To prevent loosening, apply LOCTITE 263 and LOCK PRIMER 7649 manufactured by
HENKEL JAPAN Co., Ltd. according to the Loctite Coating Procedure Manual (ETAD-C0151-00).
Spacer for assembly is available HR30-8P-T02.
Table for assembly is available HR30-7J-10PC-T01.
4 The cable pull and twisting strength and other characteristics may differ,
depending on the cable structure.
Please confirm before the use.
△2 5 The assembly this product applies to the manual ETAD-C0476-00.

Life size(1:1)



NO.	MATERIAL	FINISH , REMARKS	NO.	MATERIAL	FINISH , REMARKS
3	PBT	(Black) UL94V-0	6	PPS	(Black) UL94V-0
2	PPS	(Black) UL94V-0	5	Silicone rubber	(Black)
1	PPS	(Black) UL94V-0	4	Polyacetal	(Natural)

UNITS	SCALE		COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
mm	5 : 1	△2	2	DIS-C-00014968	HY. KISHI	HY. KOBAYASHI	20230404

HIROSE ELECTRIC CO., LTD.

APPROVED	MO. SATOH	20051021	DRAWING NO. EDC3-112266-71
CHECKED	MO. SATOH	20051021	PART NO. HR30-7J-10PC(71)
DESIGNED	EJ. KUNII	20051021	CODE NO. CL0130-2015-9-71 △2 1/1
DRAWN	EJ. KUNII	20051021	