FORM HC0011-5-7 1

Isometric Diagram **A** – **A** 4 Press fitting (89.6) Attached JRANING FO 1-5/8-18UNEF Notes 1. The contact will be sent with Ref. No. @ press-fitted to Ref. No. ③. 2. Rotation examples of ref no. ① and ② are shown. ⚠ 3. Recommended Crimping Tool: JIS-C-9711 IZUMI CO., LTD REC-Li150. Copper 3 µ m Silver plating 4. Make sure that the Keigland shell is tightened to the end of the screw. The recommended tightening torque is 6N·m. 2 PBT (Black) UL94V-0 PBT 5 UL94V-0 (Black) Furthermore, to prevent loosening, it is recommended that thread-locking fluid be used. 4 PBT 1 PBT (Black) UL94V-0 (Black) UL94V-0 5. This product is UL certified. (File E481344) REMARKS REMARKS NO. MATERIAL FINISH . NO. MATERIAL FINISH . ⚠ 6. Dropouts and the like may occur, so when mated. DESCRIPTION OF REVISIONS DESIGNED CHECKED SCALE COUNT DATE Please do not leave with the mating guide of the opposite side and the arrow marks out of alignment. UNITS YH. YAMADA 1 : 2 $|\Lambda|$ DIS-C-00002363 TP. KOMATSU 18. 08. 03 16. 08. 08 DRAWING NO. PART APPROVED : EJ. KUNII EDC-119506-00-00 HIROSE ELECTRIC CO..LTD. CHECKED : EJ. KUNII EM40M-BP-1PCA-K WARNING . This product is not hot pluggable. 16. 08. 08 NO. DESIGNED : TY. TAKAHASHI 16. 08. 08 CODE NO. :TY. TAKAHASHI CL138-0072-0-00 DRAWN