APPLICA	BLE STAN	DARD										
	OPERATING TEMPERATURE RANGE		−25 °C TO +85	°C STO		RAGE TEMPERATURE		RE	-10 °C TO +60) °C		
RATING					RANGE	RANGE						
	VOLTAGE				APPLI	CABLE	CABLE					
	CURRENT		20 A		APPLI	CABLE	WIRE		CONDUCTOR CROSS SECTI	ON 2. Omr	n ²	
					SIZE							
			SPEC	IFIC/	ATION	NS						
										QT	AT	
	RUCTION		1201 11100					. KE QO	THE WEITT O	۱ ۹.	7.11	
GENERAL EXAM		VICHALIV	AND BY MEASURING INSTRUMENT.			VCCUBD II	NG TO DR	AWING		X	Х	
	IC CHARA					100011011	iu io bit	All ING.			1 /	
		1		۸			5 mΩ l	MAY		X	Ι_	
CONTACT RESISTANCE CONTACT SHALL BE MEASURED AT DC 1 A. 5 m\(\Omega\) MAX. X MECHANICAL CHARACTERISTICS												
		l .		ıc	10	CONTACT	DECICTA	NCE ·	10 mΩ MAX.			
MECHANICAL OF	ZEKATIUN	100 11	MES INSERTIONS AND EXTRACTION	15.	U	JUNTAGT	RESISIA	INCE .	TO IIIS2 MAA.	Х	_	
COUN	T DE	SCRIPTI	ON OF REVISIONS		DESIGN	VED			CHECKED	D/	ATE	
a			OIT OI TEVIOIOTO		<i>D</i> 20.0.	122			OT ILONED	-		
							4 DDD) /ED	IIV KODAVACIII	10.0	24 01	
REMARK						APPROVED			HY. KOBAYASHI	16. 04. 01		
						DESIGNED			HY. KOBAYASHI		16. 04. 01	
									TH. KAMEYA			
						DRAWN			TH. KAMEYA 16. 03. 31			
						RAWING NO. ELC-1177			ELC-117735-	00-00	0	
						T NO			HR43-PC-111			
	SPECIFICATION SHEET PART				PART	I NO.			1. [
HRS HIROSE ELECTRIC CO.					CODE	CODE NO. CL143			8-0004-8-00	Δ	1/1	