



Mar.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.












CONSTRUCTION(REFERENCE)




D-D (REFERENCE)





CONNECTOR UNIT





E-E





NOTES.

1. THIS PRODUCT SHALL BE IN DISASSEMBLED CONDITION (EXCEPT CONNECTOR UNIT ③, ④)WHEN DELIVERED.
2. TERMINAL AREA SHALL BE COVERD WITH SHRINKAEGE TUBE AFTER SOLDERING.

NO.	MATERIAL	FINISH , REMARKS	NO.	MATERIAL	FINISH , REMARKS
4	POLYAMIDE	BLACK UL94V-0			
3	COPPER ALLOY	SELECTIVE GOLD PLATING 0.2 μm	7	STEEL	BLACK TAPPING SCREW
2	POLYCARBONATE	BLACK UL94V-0 ⚠1	6	STAINLESS STEEL	
1	POLYCARBONATE	BLACK UL94V-0 ⚠1	5	STAINLESS STEEL	

UNITS	SCALE		COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
mm	2 : 1	⚠1	2	DIS-E-004411	KG. OKITA	TA. ASO	12.11.07

HIROSE ELECTRIC CO., LTD.

APPROVED	HO. MIWA	05.01.05	DRAWING NO. EDC3-120712-02
CHECKED	YH. ENAMI	05.01.05	PART NO. 3540-10P-CV(50)
DESIGNED	TU. TANIGUCHI	05.01.05	
DRAWN	TU. TANIGUCHI	05.01.05	CODE NO. CL235-0010-4-50 ⚠1 1/1

HRS DRAWING FOR REFERENCE