Mar.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

APPLICABLE STANDARD				
RATING	OPERATING TEMPERATURE RANGE	2 −40 ℃ TO +105 ℃	STORAGE TEMPERATURE RANGE	3 −40 ℃ TO +60 ℃
	VOLTAGE		CURRENT	
			APPLICABLE WIRE	14 TO 50 sq

SPECIFICATIONS

ITEM	TEST METHOD	REQUIREMENTS	QT	AT
CONSTRUCTION				
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	X	X
MARKING	CONFIRMED VISUALLY.		X	X

	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
△0					

REMARK

1. THIS PRODUCT' s SPECIFICATIONS CONFORMS TO PS3C-*-1UP SPECIFICATIONS FOR USE IN COMBINATION WITH PS3C-*-1UP.
2. THE OPERATION TEMPERATURE INCLUDES THE TEMPERATURE RISE BY CURRENT CARRYING.
3. STORAGE TEMPERATURE RANGE SHOWS STORAGE CONDITION FOR UNUSED PRODUCTS INCLUDING PACKING MATERIALS. FOLLOW THE OPERATING TEMPERATURE RANGE FOR STORAGE CONDITION AFTER MOUNTING.

Unless otherwise specified, refer to JIS C 5402.

APPROVED	NM. NISHIMATSU	14. 07. 23
CHECKED	NM. NISHIMATSU	14. 07. 23
DESIGNED	WR. YAMADA	14. 07. 22
DRAWN	WR. YAMADA	14. 07. 22

Note QT:Qualification Test AT:Assurance Test X:Applicable Test

HRS	SPECIFICATION SHEET	DRAWING NO.	ELC4-128556-00
		PART NO.	PS3C-1UP-CVL
	HIROSE ELECTRIC CO., LTD.	CODE NO	CL236-1066-0-00 △0 1/1

FORM HD0011-2-1