

APPLICABLE STANDARD					
RATING	OPERATING TEMPERATURE RANGE	<div>2</div> -40 °C TO +105 °C	STORAGE TEMPERATURE RANGE	<div>3</div> -40 °C TO +60 °C	
	VOLTAGE		CURRENT		
			APPLICABLE WIRE		
SPECIFICATIONS					
ITEM		TEST METHOD	REQUIREMENTS	QT	AT
CONSTRUCTION					
GENERAL EXAMINATION		VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	X	X
MARKING		CONFIRMED VISUALLY.		X	X
	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
<div>△</div>					
<div>REMARK</div> <div>1. THIS PRODUCT' s SPECIFICATIONS CONFORMS TO PS3C-*1UP SPECIFICATIONS FOR USE IN COMBINATION WITH PS3C-*1UP AND PS3C-1UP-CVL.</div> <div><div>2</div> THE OPERATION TEMPERATURE INCLUDES THE TEMPERATURE RISE BY CURRENT CARRYING.</div> <div><div>3</div> STORAGE TEMPERATURE RANGE SHOWS STORAGE CONDITION FOR UNUSED PRODUCTS INCLUDING PACKING MATERIALS.FOLLOW THE OPERATING TEMPERATURE RANGE FOR STORAGE CONDITION AFTER MOUNTING.</div> <div>Unless otherwise specified, refer to JIS C 5402.</div>			APPROVED	NM. NISHIMATSU	14. 10. 02
			CHECKED	NM. NISHIMATSU	14. 10. 02
			DESIGNED	WR. YAMADA	14. 10. 02
			DRAWN	WR. YAMADA	14. 10. 02
			Note QT:Qualification Test AT:Assurance Test X:Applicable Test		
<div>HRS</div>	SPECIFICATION SHEET		PART NO.	PS3C-1UP-TS	
	HIROSE ELECTRIC CO., LTD.		CODE NO	CL236-1068-6-00	<div>△</div> 1/1