




Mar.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.













2 BUSHING, ASSEMBLY DIMENSIONS DOR REFERENCE





HRS DRAWING FOR REFERENCE

NOTE
1 LESS TEAN Ø4 mm IS PRESUMED CABLE SIZE.
2 CABLE SHALL BE OVERMOLDED WITH BUSHING TO FIX.
USE NON-MIGRATION RESIN FOR OVERMOLDING.
3 CONTACT AREA:GOLD PLATED 0.2μm MIN.
LEAD AREA :GOLD PLATED FLASH.
UNDER PLATING:NICKEL PLATED 2μm MIN.
1 4 REFER TO THE TECHNICAL SPECIFICATION(ETAP-E3217)FOR PACKING.

NO.	MATERIAL	FINISH , REMARKS	NO.	MATERIAL	FINISH , REMARKS
4	PC	(BLACK)UL94V-0	8	STEEL	BLACK CHROMATE Cr3.(TAPPING SCREW)
3	PA	(BLACK)UL94V-0	7	STAINLESS STEEL	
2	COPPER ALLOY	3	6	STAINLESS STEEL	
1	COPPER ALLOY	3	5	PC	(BLACK)UL94V-0

UNITS	SCALE		COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
mm	2 : 1	1	1	DIS-E-00009892	KN. ICHIKAWA	KG. OKITA	20220624

HIROSE ELECTRIC CO., LTD.

APPROVED	NM. NISHIMATSU	20151027	DRAWING NO. EDC-124681-30-00
CHECKED	KN. ICHIKAWA	20151027	PART NO. ST40-10S-CVR(30)
DESIGNED	TS. ITO	20151027	CODE NO. CL0241-0040-7-30
DRAWN	AK. AKIYAMA	20151027	1 1/1