



Mar.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

HRS DRAWING FOR REFERENCE













2 ASSEMBLED









NOTE 1. THIS PRODUCT IS DELIVERED SEPARATELY.
1 2 AS SHOWN IN THE FIGURE, THIS PRODUCT SHALL BE USED ASSEMBLED TO A CONNECTOR UNIT 'DH40-17S' or 'DH3*B-17S'. A CLAMP 'DH-17-CMB(6.3)' IS NEEDED WHEN ASSEMBLING THE UNIT.
3. THIS PRODUCT SHALL BE MATED WITH A RECEPTACLE 'DH60-17P*' WHICH ASSEMBLED LOCK SCREWS 'DH-LNA***'.
4 A RECOMMENDED SCREW TIGHTENING TORQUE TO THE LOCK SCREWS TO BE FROM 0.06 TO 0.07 N・m.
5 A RECOMMENDED SCREW TIGHTENING TORQUE FOR COVERS TO BE FROM 0.1 TO 0.15 N・m.

NO.	MATERIAL	FINISH , REMARKS
3	STAINLESS STEEL	PLATING : NICKEL 0.1μm MIN
2	PC	UL94V-0 (SAND BEIGE)
1		

NO.	MATERIAL	FINISH , REMARKS
5	STEEL	OVER PLATING: NICKEL 3μm MIN UNDER PLATING: COPPER 0.1μm MIN
4	STEEL	OVER PLATING : NICKEL 2μm MIN UNDER PLATING : COPPER 1μm MIN M2×0.4

UNITS	SCALE		COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
mm	2 : 1	1	1	DIS-E-00002570	TS. ITO	TU. TANIGUCHI	20191007

HIROSE ELECTRIC CO., LTD.

APPROVED	KN. ICHIKAWA	20100405
CHECKED	KN. ICHIKAWA	20100405
DESIGNED	MO. SHIMOYAMA	20100405
DRAWN	TM. ONO	20100405


DRAWING NO.	EDC-126586-13-13
PART NO.	DH-17-CV1B(13)
CODE NO.	CL244-0009-6-13

1 1/2


Mar.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demands high reliability, kindly contact our sales window correspondents.

HRS DRAWING FOR REFERENCE


REF No. 1




REF No. 2




REF No. 3



REF No. 4



REF No. 5



DRAWING NO.	EDC-126586-13-13
PART NO.	DH-17-CV1B(13)
CODE NO.	CL244-0009-6-13

1 2/2