



Feb.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.










2 ASSEMBLED



HRS DRAWING FOR REFERENCE

NOTE 1 THIS PRODUCT IS DELIVERED SEPARATELY.
2 AS SHOWN IN THE FIGURE, THIS PRODUCT SHALL BE USED ASSEMBLED TO A CONNECTOR UNIT "DH3*B-17S".
A CLAMP "DH-17-CMB(6.3)" IS NEEDED WHEN ASSEMBLING THE UNIT.
3 A RECOMMENDED SCREW TIGHTENING FOR COVERS TO BE FROM 0.1 TO 0.15 N・m.

NO.	MATERIAL	FINISH , REMARKS	NO.	MATERIAL	FINISH , REMARKS
3	STAINLESS STEEL	PLATING : NICKEL 0.1μm MIN.	6	STEEL	PLATING : NICKEL
2	PC	UL94V-0 (SAND BEIGE)	5	PC	UL94V-0 (SAND BEIGE)
1			4	STAINLESS STEEL	


UNITS	SCALE	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
mm	2 : 1					


HIROSE ELECTRIC CO., LTD.


APPROVED	AO. SUZUKI	10.04.07	DRAWING NO. EDC3-126946-13
CHECKED	AH. KODAMA	10.04.07	PART NO. DH-17-CT2B(13)
DESIGNED	MO. SHIMOYAMA	10.04.07	
DRAWN	TM. ONO	10.04.07	CODE NO. CL244-0047-5-13


Feb.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

HRS DRAWING FOR REFERENCE









HRS	DRAWING NO.	EDC3-126946-13
	PART NO.	DH-17-CT2B(13)
	CODE NO.	CL244-0047-5-13 △ 2/2