



Mar.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.









RECOMENDED PATTERN





APPLICATION DRAWING



HRS DRAWING FOR REFERENCE

NOTE1: WHEN THIS CONNECTOR MATES WITH DF13-4S-1.25C,
THE MATING HEIGHT IS 5.8mm
2: LEAD CO-PLANALITY INCLUDE REINFORCED METAL
FITTINGS SHALL BE 0.1mm MAX.


NO.	MATERIAL	FINISH , REMARKS	NO.	MATERIAL	FINISH , REMARKS
2	BRASS	SURFACE PLATING : GOLD PLATING 0.76μm min. UNDER PLATING : NICKEL PLATING 0.5μm min.	5	POLYESTER	CLEAR(COVER TAPE)
			4	PS	CLEAR(EMBOSSED CARRIER TAPE)
1	POLYAMIDE	UL94-V0	3	PHOSPHOR BRONZE	SURFACE PLATING : TIN PLATING 1μm min.


UNITS	SCALE		COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
mm	5 : 1	△					

HIROSE ELECTRIC CO., LTD.


APPROVED	KI. AKIYAMA	14.04.04	DRAWING NO. EDC3-083412-02
CHECKED	TS. FUKUSHIMA	14.04.04	PART NO. DF13C-4P-1.25V(77)
DESIGNED	ST. SATO	14.04.04	
DRAWN	ST. SATO	14.04.04	CODE NO. CL536-0403-8-77 △ 1/2

Mar.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.






STYLE AND DIMENSION OF REEL



5 DETAIL OF PART NO. LABEL

DATE OF MANUFACTURED	** ** **
CODE NO.	CL536-0403-8-77
PART NO.	DF13C-4P-1.25V(77)
QUANTITY	1000 KO
SUPPLIER	HIROSE ELECTRIC CO.,LTD.


HRS DRAWING FOR REFERENCE



DIRECTION OF UNREELING

NOTES 3 : 1REEL:1000 CONNECTORS.
4 : AT THE BEGINNING OF THE REEL, 30 COMPONENTS SHALL BE EMPTY.
AT THE END OF THE REEL, 20 COMPONENTS SHALL BE EMPTY.
5 : DETAIL OF PART NO. LABEL IS WRITTEN IN JAPANESE.

C-C



DRAWING NO.	EDC3-083412-02
PART NO.	DF13C-4P-1.25V(77)
CODE NO.	CL536-0403-8-77

△ 2/2

FORM HC0011-5-8