




Mar.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.













3 RECOMMENDED PATTERN



APPLICATION DRAWING



NOTES 1 : WHEN THIS CONNECTOR MATES WITH DF13-8S-1.25C, THE MATING HEIGHT IS 5.8mm.
2 : LEAD CO-PLANARITY INCLUDING REINFORCED METAL FITTINGS SHALL BE WITHIN 0.1mm.
3 : RECOMMENDED THICKNESS OF CREAM SOLDER PASTE:0.15mm ~ 0.2mm
OPEN AREA RATIO:100%

NO.	MATERIAL	FINISH , REMARKS	NO.	MATERIAL	FINISH , REMARKS
2	BRASS	SURFACE:TIN PLATED 1μm min.	4	PS	EMBOSSED CARRIER TAPE, CLEAR
1	POLYAMIDE	UL94V-0, BEIGE	3	PHOSPHOR BRONZE	SURFACE:TIN PLATED 1μm min.
			5	POLYESTER	COVER TAPE, CLEAR

UNITS	SCALE	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
mm	5 : 1					

HIROSE ELECTRIC CO., LTD.

APPROVED	TS. SAKATA	08. 09. 01
CHECKED	TS. KUMAZAWA	08. 08. 29
DESIGNED	SN. KOBAYASHI	08. 08. 26
DRAWN	SN. KOBAYASHI	08. 08. 26


DRAWING NO. EDC3-083416-01
PART NO. DF13C-8P-1.25V(21)
CODE NO. CL536-0407-9-21
1/2


FORM HC0011-5-7

HRS DRAWING FOR REFERENCE


Mar.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

A PORTION (FREE)






DIRECTION OF UNREELING



STYLE AND DIMENSION OF REEL (FREE)



6 DETAIL OF PART No. LABEL

- SUPPLIER
- QUANTITY
- PART No.
- CODE No.
- DATE OF MANUFACTURED

生産月日	年　月　日
図番	CL536-0407-9-21
品番	DF13C-8P-1.25V(21)
納入数量	1000ko
納入者	ヒロセ電機(株)

NOTES 4 : 1REEL:1000 CONNECTORS.
5 : AT THE BEGINNING OF THE REEL, 30 COMPONENTS SHALL BE EMPTY.
AT THE END OF THE REEL, 20 COMPONENTS SHALL BE EMPTY.
6 : DETAIL OF PART No. LABEL IS WRITTEN IN JAPANESE.

HRS DRAWING FOR REFERENCE

DRAWING NO.	EDC3-083416-01
PART NO.	DF13C-8P-1.25V(21)
CODE NO.	CL536-0407-9-21

△ 2/2